# Olive oil




# Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

# PRODUCT NAME

Olive oil

# STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.



# SUPPLIER

Company: Santa Cruz Biotechnology, Inc. Address: 2145 Delaware Ave Santa Cruz, CA 95060 Telephone: 800.457.3801 or 831.457.3800 Emergency Tel: CHEMWATCH: From within the US and Canada: 877-715-9305


Emergency Tel: From outside the US and Canada: +800 2436 2255 (1-800-CHEMCALL) or call +613 9573 3112

#### **PRODUCT USE**

Oil obtained from ripe olives of the cultivated oil tree Olea europaea L., oleaceae. Directly as food, as cooking oil and emulsified in mayonnaise, dressings. Carrier for oil soluble food dyes. Emollient, laxative.

#### SYNONYMS

"fixed oil olive oil BP", "Gold Cross Olive Oil"



# **Section 2 - HAZARDS IDENTIFICATION**



# EMERGENCY OVERVIEW RISK

# POTENTIAL HEALTH EFFECTS

# ACUTE HEALTH EFFECTS

#### SWALLOWED

# Overexposure is unlikely in this form.

• The material has NOT been classified as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, unintentional ingestion is not thought to be cause for concern.

■ Use in food, and as food additive indicates high degree of tolerance.

#### EYE

Although the liquid is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn).

#### SKIN

• Skin contact is not thought to have harmful health effects, however the material may still produce health damage following entry through wounds, lesions or abrasions.

• Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

• There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterized by redness, swelling and blistering.

#### INHALED

• The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Inhalation of oil droplets/ aerosols may cause discomfort and may produce chemical pneumonitis.

■ Fine mists generated from plant/ vegetable (or more rarely from animal) oils may be hazardous. Extreme heating for prolonged periods, at high temperatures, may generate breakdown products which include acrolein and acrolein-like substances.

#### **CHRONIC HEALTH EFFECTS**

• Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Synthetic 1,2-diglycerides of short chain (C6, C8, C10) fatty acids are activators of protein kinase C (PKC). PKC is a serine-threonine kinase which also requires calcium ion for its activation. Activated PKC phosphorylates proteins of the cellular signal cascade, which eventually induce expression of growth regulatory genes. This, in turn, may promote the growth of tumours. Structural analogues of the 1,2-diglycerides, such as the phorbol esters, have been shown to strongly promote such an event.

Glyceryl dilaurate, glyceryl diarachidate, glyceryl dibehenate, glyceryl dierucate, glyceryl dihydroxystearate, glyceryl diisopalmitate, glyceryl diisostearate, glyceryl diinoleate, glyceryl dimyristate, glyceryl dioleate, glyceryl diricinoleate, glyceryl dipalmitoleate, glyceryl distearate, glyceryl palmitate lactate, glyceryl stearate citrate, glyceryl stearate lactate, and glyceryl stearate succinate are diacylglycerols (also known as diglycerides or glyceryl diesters) that function as skin conditioning agents-emollients in cosmetics. Only glyceryl dilaurate (up to 5%), glyceryl diisostearate (up to 43%), glyceryl dioleate (up to 2%), glyceryl distearate (up to 7%), and glyceryl stearate lactate (up to 5%) are reported to be in current use. Production proceeds from fully refined vegetable oils, which are further processed using hydrogenation and fractionation techniques, and the end products are produced by reacting selected mixtures of the partly hydrogenated, partly fractionated oils and fats with vegetable-derived glycerine to yield partial glycerides. In the final stage of the production process, the products are purified by deodorization, which effectively removes pesticide residues and lower boiling residues such as residues of halogenated solvents and aromatic solvents. Diglycerides have been approved by the Food and Drug Administration (FDA) for use as indirect food additives. Nominally, these ingredients are 1,3-diglycerides, but are easily isomerised to the 1,2-diglycerides form. The 1,3-diglyceride isomer is not a significant toxicant in acute, short-term, subchronic, or chronic animal tests. Glyceryl dilaurate was a mild primary irritant in albino rabbits, but not a skin sensitiser in guinea pig maximization tests. Diacylglycerol oil was not genotoxic in the Ames test, in mammalian Chinese hamster lung cells, or in a rodent bone marrow micronucleus assay. An eye shadow containing 1.5% glyceryl dilaurate did not induce skin irritation in a single insult patch test, but mild skin irritation reactions to a foundation containing the same concentration were observed. A trade mixture containing an unspecified concentration of glyceryl dibehenate did not induce irritation or significant cutaneous intolerance in a 48-h occlusive patch test. In maximization tests, neither an eye shadow nor a foundation containing 1.5% glyceryl dilaurate was a skin sensitiser. Sensitisation was not induced in subjects patch tested with 50% w/w glyceryl dioleate in a repeated insult, occlusive patch test. Glyceryl palmitate lactate (50% w/v) did not induce skin irritation or sensitization in subjects patch tested in a repeat-insult patch test. Phototoxicity or photoallergenicity was not induced in healthy volunteers tested with a lipstick containing 1.0% Glyceryl rosinate. Two diacylglycerols, 1-oleoyl-2-acetoyl-sn-glycerol and 1,2-dipalmitoyl-sn-glycerol, did not alter cell proliferation (as determined by DNA synthesis) in normal human dermal fibroblasts in vitro at doses up to 10 µg/ml. In the absence of initiation, Glyceryl distearate induced a moderate hyperplastic response in randomly bred mice of a tumor-resistant strain, and with 9,10-dimethyl-1,2-benzanthracene (DMBA) initiation, an increase in the total cell count was observed. In a glyceryl monoester study, a single application of DMBA to the skin followed by 5% glyceryl stearate twice weekly produced no tumors, but slight epidermal hyperplasia at the site of application. Glyceryl dioleate induced transformation in 3-methylcholanthrene-initiated BALB/3T3 A31-1-1 cloned cells in vitro. A tumourpromoting dosing regimen that consisted of multiple applications of 10 µmol of a 1,2-diacylglycerol (sn-1,2-didecanoylglycerol) to female mice twice daily for 1 week caused more than a 60% decrease in protein kinase C (PKC) activity and marked epidermal hyperplasia. Applications of 10 umol sn-1,2-didecanoylglycerol twice weekly for 1 week caused a decrease in cytosolic PKC activity, an increase in particulate PKC activity, and no epidermal hyperplasia. In studies of the tumour-promoting activity of 1,2-diacylglycerols, dose and the exposure regimen by which the dose is delivered play a role in tumor promotion. The 1,2-diacylglycerol-induced activation of PKC may also relate to the saturation of the fatty acid in the 1 or 2 position; 1,2-Diacylolycerols with two saturated fatty acids are less effective. Also, the activity of 1,2-diacylglycerols may be reduced when the fatty acid moiety in the structure is a long-chain fatty acid. A histological evaluation was performed on human skin from female volunteers (18 to 56 years old) who had applied a prototype lotion or placebo formulation, both containing 0.5% Glyceryl Dilaurate, consecutively for 16 weeks or 21 weeks. Skin irritation was not observed in any of the subjects tested. Biopsies (2 mm) taken from both legs of five subjects indicated no recognizable abnormalities of the skin; the epidermis was normal in thickness, and there was no evidence of scaling, inflammation, or neoplasms in any of the tissues that were evaluated. The available safety test data indicate that diglycerides in the 1,3-diester form do not present any significant acute toxicity risk, nor are these ingredients irritating, sensitizing, or photosensitising. Whereas no data are available regarding reproductive or developmental toxicity, there is no reason to suspect any such toxicity because the dermal absorption of these chemicals is negligible. 1,3-Diglycerides contain 1,2-diglycerides, raising the concern that 1,2-diglycerides could potentially induce hyperplasia. Data regarding the induction of PKC and the tumour promotion potential of 1,2-diacylglycerols increases the level of concern. Most of the diglycerides considered above, however, have fatty acid chains longer than 14 carbons and none have mixed saturated/unsaturated fatty acid moieties. In a 21-week use study of a prototype lotion containing 0.5% glyceryl dilaurate (a 14-carbon chain fatty acid) indicated no evidence of scaling, inflammation, or neoplasms in biopsy specimens. Also, DNA synthesis assays on glyceryl dilaurate and glyceryl distearate indicated that neither chemical altered cell proliferation (as determined by DNA synthesis) in normal human dermal fibroblasts in vitro at doses up to 10 ug/ml. However the concentration of these ingredients can vary (up to 43% for glyceryl diisostearate in lipstick), the frequency of application can be several times daily, and the proportion of diglycerides that are inactive 1,3 isomers versus potentially biologically active 1,2 isomers is unknown; as a precaution it is believed that each use should be examined to ensure the absence of epidermal hyperplasia during product development and testing. In the absence of inhalation toxicity data on the glyceryl diesters it is thought that these ingredients can be used safely in aerosolised products because they are not respirable. Although there are gaps in knowledge about product use, the overall information available on the types of products in which these ingredients are used and at what concentration indicate a pattern of use. Within this overall pattern of use, the CIR Expert Panel considers all ingredients in this group to be safe.

International Journal of Toxicology, Vol. 26, No. 3 Suppl, 1-30 (2007).

Glyceryl triesters (triglycerides), following ingestion, are metabolised to monoglycerides, free fatty acids and glycerol, all of which are absorbed in the intestinal mucosa and undergo further metabolism. Little or no acute, subchronic or chronic oral toxicity was seen in animal studies unless levels approached a significant percentage of calorific intake. Subcutaneous injections of tricaprylin in rats over a five-week period caused granulomatous reaction characterised by oil deposits surrounded by macrophages. Diets containing substantial levels of tributyrin produced gastric lesions in rats fed for 3-35 weeks; the irritative effect of the substance was thought to be the cause of tissue damage.

Dermal application was not associated with significant irritation in rabbit skin; ocular exposures were, at most, mildly irritating to rabbit eyes. No evidence of sensitisation or photosensitisation was seen in a guinea pig maximisation test. Most of the genotoxicity test systems were negative. Tricaprylin, trioctanoin and triolein have been used, historically, as vehicles in carcinogenicity testing of other chemicals. In one study, subcutaneous injection of tricaprylin, in newborn mice, produced more tumours in lymphoid tissue than were seen in untreated animals whereas, in another study, subcutaneous or intraperitoneal injection in 4- to 6-week old female mice produced no tumours. Trioctanoin injected subcutaneously in hamster produced no tumours; when injected intraperitoneally in pregnant rats there was an increase in mammary tumours among the off-spring but similar studies in pregnant hamsters and rabbits showed no tumours in the off-spring.

The National Toxicological Program conducted a 2-year study in rats given tricaprylin by gavage. The treatment was associated with a statistically significant dose-related increase in pancreatic acinar cell hyperplasia and adenoma but there were no acinar carcinomas.

Tricaprylin is not teratogenic to mice or rats but some reproductive effects were seen in rabbits. A low level of foetal eye abnormalities and a small percentage of abnormal sperm were reported in mice injected with trioctanoin.

| NAME                                      | CAS RN    | %   |
|---|-----------|-----|
| olive oil                                 | 8001-25-0 | 100 |
| fixed oil with composition:               |           |     |
| mixed glycerides of oleic acid - 83.5%    |           |     |
| mixed glycerides of palmitic acid - 9.4%  |           |     |
| mixed glycerides of linoleic acid - 4.0%  |           |     |
| mixed glycerides of stearic acid - 2.0%   |           |     |
| mixed glycerides of arachidic acid - 0.9% |           |     |
| squalene - < 0.7%                         |           |     |
| phytosterols - }0.2%                      |           |     |
| tocopherols }                             |           |     |

# Section 4 - FIRST AID MEASURES

# SWALLOWED

- Immediately give a glass of water.

• First aid is not generally required. If in doubt, contact a Poisons Information Center or a doctor.

# EYE

- If this product comes in contact with eyes:
- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

# SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

# INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

# NOTES TO PHYSICIAN

Treat symptomatically.

# **Section 5 - FIRE FIGHTING MEASURES**

| Vapour Pressure (mmHG):     | Negligible     |  |
|-----------------------------|----------------|--|
| Upper Explosive Limit (%):  | Not available. |  |
| Specific Gravity (water=1): | 0.914-0.919    |  |
| Lower Explosive Limit (%):  | Not available. |  |

# **EXTINGUISHING MEDIA**

- •
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

# FIRE FIGHTING

- •
- Alert Emergency Responders and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

# GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

-

# Combustible.

- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO2), acrolein, other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

#### FIRE INCOMPATIBILITY

Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

# PERSONAL PROTECTION

Glasses: Chemical goggles. Gloves: Respirator: Type A-P Filter of sufficient capacity

# Section 6 - ACCIDENTAL RELEASE MEASURES

# MINOR SPILLS

- Slippery when spilt.
- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapors and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labeled container for waste disposal.
- MAJOR SPILLS
- Slippery when spilt.


CARE: Absorbent material wet with occluded oil must be wet with water as they may auto-oxidize, become self heating and ignite.

Some oils slowly oxidize when spread in a film and oil on cloths, mops, absorbents may auto-oxidize and generate heat, smoulder, ignite and burn. In the workplace oily rags should be collected and immersed in water.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Emergency Responders and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources. Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labeled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labeled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

# **PROTECTIVE ACTIONS FOR SPILL**



From IERG (Canada/Australia) Isolation Distance -Downwind Protection Distance -

From US Emergency Response Guide 2000 Guide No guide found.

# FOOTNOTES

1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.

2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.

3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.

4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills". LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.

5 Guide No guide found. is taken from the US DOT emergency response guide book.

6 IERG information is derived from CANUTEC - Transport Canada.

# ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and

reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects

or an impaired ability to escape. AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

# Section 7 - HANDLING AND STORAGE

# **PROCEDURE FOR HANDLING**

- DO NOT allow clothing wet with material to stay in contact with skin

Rags wet / soaked with unsaturated hydrocarbons / drying oils may auto-oxidise; generate heat and, in-time, smoulder and ignite. This is especially the case where oil-soaked materials are folded, bunched, compressed, or piled together - this allows the heat to accumulate or even accelerate the reaction

Oily cleaning rags should be collected regularly and immersed in water, or spread to dry in safe-place away from direct sunlight or stored, immersed, in solvents in suitably closed containers.

- Avoid all personal contact, including inhalation.
- · Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

# **RECOMMENDED STORAGE METHODS**

- Glass container.
- Metal can or drum
- · Packing as recommended by manufacturer.
- Check all containers are clearly labeled and free from leaks.

#### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

# SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

# Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **EXPOSURE CONTROLS**

The following materials had no OELs on our records • olive oil: CAS:8001-25-0 CAS:84012-27-1

MATERIAL DATA OLIVE OIL: • Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- · cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

vegetable oil mists (except castor, cashew nut and similar irritant oils)TLV TWA: 10 mg/m3 ES TWA: 10 mg/m3 OSHA PEL TWA: 15 mg/m3, total particulate; 5 mg/m3, respirable particulate The common vegetable oil mists are considered "nuisance" particulates which have little adverse effect on the lung. They do not produce toxic effects or significant organic disease when exposures are kept under reasonable control. Direct instillation of vegetable oils into rabbit lungs produces acute bronchitis whilst high oral doses are laxatives.

### PERSONAL PROTECTION



Consult your EHS staff for recommendations

#### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

# HANDS/FEET

■ Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and

dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

#### OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.

# • Eye wash unit.

# RESPIRATOR

• Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Breathing Zone Level ppm<br>(volume) | Maximum Protection Factor | Half-face Respirator | Full-Face Respirator |
|--------------------------------------|---------------------------|----------------------|----------------------|
| 1000                                 | 10                        | A-1 P                | -                    |
| 1000                                 | 50                        | -                    | A-1 P                |
| 5000                                 | 50                        | Airline*             | -                    |
| 5000                                 | 100                       | -                    | A-2 P                |
| 10000                                | 100                       | -                    | A-3 P                |

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand.

100+

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

# ENGINEERING CONTROLS

■ General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear an approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant:   | Air Speed:                         |
|--|------------------------------------|
| solvent, vapors, degreasing etc., evaporating from tank (in still air)   | 0.25-0.5 m/s (50-100 f/min)        |
| aerosols, fumes from pouring operations, intermittent container filling,<br>low speed conveyer transfers, welding, spray drift, plating acid<br>fumes, pickling (released at low velocity into zone of active<br>generation) | 0.5-1 m/s (100-200 f/min.)         |
| direct spray, spray painting in shallow booths, drum filling, conveyer<br>loading, crusher dusts, gas discharge (active generation into zone of<br>rapid air motion)   | 1-2.5 m/s (200-500 f/min)          |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).   | 2.5-10 m/s (500-2000 f/min.)       |
| Within each range the appropriate value depends on:  |                                    |
| Lower end of the range   | Upper end of the range             |
| 1: Room air currents minimal or favorable to capture   | 1: Disturbing room air currents    |
| 2: Contaminants of low toxicity or of nuisance value only  | 2: Contaminants of high toxicity   |
| 3: Intermittent, low production.   | 3: High production, heavy use      |
| 4: Large hood or large air mass in motion  | 4: Small hood - local control only |

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Care: Atmospheres in bulk storages and even apparently empty tanks may be hazardous by oxygen depletion. Atmosphere must be checked before entry.

Requirements of State Authorities concerning conditions for tank entry must be met. Particularly with regard to training of crews for tank entry; work permits; sampling of atmosphere; provision of rescue harness and protective gear as needed.

# Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

# PHYSICAL PROPERTIES

| Liquid.<br>Does not mix with water.<br>Floats on water. |                |                                |                 |
|---|----------------|--------------------------------|-----------------|
| State   | Liquid         | Molecular Weight               | Not applicable. |
| Melting Range (°F)                                      | <32            | Viscosity                      | Not Available   |
| Boiling Range (°F)                                      | Not available. | Solubility in water (g/L)      | Immiscible      |
| Flash Point (°F)  | 437            | pH (1% solution)               | Not applicable  |
| Decomposition Temp (°F)                                 | Not available  | pH (as supplied)               | Not applicable  |
| Autoignition Temp (°F)                                  | 649.994        | Vapour Pressure (mmHG)         | Negligible      |
| Upper Explosive Limit (%)                               | Not available. | Specific Gravity (water=1)     | 0.914-0.919     |
| Lower Explosive Limit (%)                               | Not available. | Relative Vapor Density (air=1) | Not applicable. |
| Volatile Component (%vol)                               | Negligible     | Evaporation Rate               | Slow.           |

#### APPEARANCE

Pale yellow to light-green oil; floats on water. Slight characteristic odour and taste. Miscible with ether, chloroform carbon disulfide. Becomes rancid on exposure to air. Becomes turbid at about 5 deg C.

# Section 10 - CHEMICAL STABILITY

# CONDITIONS CONTRIBUTING TO INSTABILITY

- - Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

#### STORAGE INCOMPATIBILITY

Vegetable oils and some animal fats undergo undesirable deterioration reactions in the presence of oxygen from the air becoming rancid accompanying off-flavours and smells.

The mechanism of autoxidation of vegetable oils is classically regarded as following a number of stages being:

- a usually slow initiation phase
- a usually rapid propagation
- and a termination phase

The initiation phase involves the formation of a free radical from a triglyceride molecule in the fat: this may be promoted by the presence of heavy metals in the oil, or by heat or light. The next stage is the reaction of the triglyceride free radical with oxygen to produce a peroxide free radical, which can react with another triglyceride to produce a hydroperoxide and another triglyceride free radical. Steps 2 and 3 can repeat in a chain reaction until two peroxy free radicals collide and neutralise each other.

Some drying oils produce cyclic peroxides instead of hydroperoxides.

Autooxidation may also occur in saturated fatty acids and their esters. Monohydroperoxides are formed. Although all carbon atoms are subject to oxidation, preferential oxidation appears to occur towards the centre of the molecule.

Autoxidation is assisted by higher ambient temperatures (the rate doubling for every ten degrees Centigrade rise) and by the presence of heavy metal ions, especially copper. The degree of unsaturation of the oil is also relevant to shelf-life; oils with a high linolenic fatty acid content (3 double bonds) being more prone that those with a higher saturated fatty acid content. Autoxidation can be minimized by the presence of anti-oxidants, which can act as free-radical inhibitors. Vegetable oils should therefore be stored in a cool place away from heat and light, and should only come into contact with inert (glass of stainless steel) containers which will not leach heavy metals. Blanketing under nitrogen should be considered in bulk storages.

Food grade materials must be protected from all possible contaminants.

Avoid reaction with oxidizing agents.

• Materials soaked with plant/ vegetable derived (and rarely, animal) oils may undergo spontaneous combustion

For incompatible materials - refer to Section 7 - Handling and Storage.

# Section 11 - TOXICOLOGICAL INFORMATION

#### OLIVE OIL

#### TOXICITY AND IRRITATION

No significant acute toxicological data identified in literature search.

# Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows: OLIVE OIL:

• Unsaturated vegetable oils are often used in paints which upon "drying" produce a polymeric network formed of the constituent fatty acids. During the drying process, a number of compounds are produced that do not contribute to the polymer network. These include unstable hydroperoxide (ROOH) the major by-product of the reaction of oxygen with unsaturated fatty acids. The hydroperoxides quickly decompose, forming carbon dioxide and water, as well as a variety of aldehydes, acids and hydrocarbons. Many of these compounds are volatile, and in an unpigmented oil, they would be quickly lost to the environment. However, in paints, such volatiles may react with lead, zinc, copper or iron compounds in the pigment, and remain in the paint film as coordination complexes or salts. A large number of the original ester bonds in the oil molecules undergo hydrolysis releasing individual fatty acids. Some portion of the free fatty acids react with metals in the pigment, producing metal carboxylates. Together, the various non-cross-linking substances associated with the polymer network constitute the mobile phases. Unlike the molecules that are part of the network itself, they are capable of moving and diffusing within the film, and can be removed using heat or a solvent. The mobile phase may play a role in plasticising the paint film, preventing it from becoming too brittle.

One simple technique for monitoring the early stages of the drying process is to measure weight change in an oil film over time. Initially, the film becomes heavier, as it absorbs large amounts of oxygen. Then oxygen uptake ceases, and the weight of the film declines as volatile compounds are lost to the environment.

As the oil ages, a further transition occurs. Carboxyl groups in the polymers of the stationary phase lose a hydrogen ion, becoming negatively charged, and form complexes with metal cations present in the pigment. The original network, with its nonpolar, covalent bonds is replaced by an ionomeric structure, held together by ionic interactions. At present, the structure of these ionomeric networks is not well understood.

• Substances containing unsaturated carbons are ubiquitous in indoor environments. They result from many sources (see below). Most are reactive with environmental ozone and many produce stable products which are thought to adversely affect human health. The potential for surfaces in an enclosed space to facilitate reactions should be considered.

| Source of unsaturated substances              | Unsaturated substances (Reactive Emissions)   | Major Stable Products produced following reaction with ozone.   |
|---|---|---|
| Occupants (exnaled breath, ski olis, personal | Isoprene, nitric oxide, squalene, unsaturated sterols, oleic acid and other unsaturated fatty | Methacrolein, methyl vinyl ketone, nitrogen<br>dioxide, acetone, 6MHQ, geranyl acetone,<br>4OPA, formaldehyde, nonanol, decanal,<br>9-oxo-nonanoic acid, azelaic acid, nonanoic |

|  |  | acid.  |
|--|--|--|
| Soft woods, wood flooring, including cypress, cedar and silver fir boards, houseplants | Isoprene, limonene, alpha-pinene, other terpenes and sesquiterpenes  | Formaldehyde, 4-AMC, pinoaldehyde, pinic<br>acid, pinonic acid, formic acid, methacrolein,<br>methyl vinyl ketone, SOAs including ultrafine<br>particles   |
| Carpets and carpet backing   | 4-Phenylcyclohexene, 4-vinylcyclohexene,<br>styrene, 2-ethylhexyl acrylate, unsaturated<br>fatty acids and esters                                      | Formaldehyde, acetaldehyde, benzaldehyde, hexanal, nonanal, 2-nonenal  |
| Linoleum and paints/polishes containing linseed oil                                    | Linoleic acid, linolenic acid  | Propanal, hexanal, nonanal, 2-heptenal,<br>2-nonenal, 2-decenal, 1-pentene-3-one,<br>propionic acid, n-butyric acid  |
| Latex paint  | Residual monomers  | Formaldehyde   |
| Certain cleaning products, polishes, waxes, ai<br>fresheners                           | Limonene, alpha-pinene, terpinolene, alpha-<br>r terpineol, linalool, linalyl acetate and other<br>terpenoids, longifolene and other<br>sesquiterpenes | Formaldehyde, acetaldehyde, glycoaldehyde,<br>formic acid, acetic acid, hydrogen and organic<br>peroxides, acetone, benzaldehyde, 4-hydroxy-<br>4-methyl-5-hexen-1-al, 5-ethenyl-dihydro-<br>5-methyl-2(3H)-furanone, 4-AMC, SOAs<br>including ultrafine particles |
| Natural rubber adhesive  | Isoprene, terpenes   | Formaldehyde, methacrolein, methyl vinyl ketone  |
| Photocopier toner, printed paper, styrene polymers                                     | Styrene  | Formaldehyde, benzaldehyde   |
| Environmental tobacco smoke  | Styrene, acrolein, nicotine  | Formaldehyde, benzaldehyde, hexanal, glyoxal, N-methylformamide, nicotinaldehyde, cotinine   |
| Soiled clothing, fabrics, bedding  | Squalene, unsaturated sterols, oleic acid and other saturated fatty acids  | Acetone, geranyl acetone, 6MHO, 40PA,<br>formaldehyde, nonanal, decanal, 9-oxo-<br>nonanoic acid, azelaic acid, nonanoic acid  |
| Soiled particle filters  | Unsaturated fatty acids from plant waxes, leaf litter, and other vegetative debris; soot; diesel particles   |  |
| Ventilation ducts and duct liners  | Unsaturated fatty acids and esters,<br>unsaturated oils, neoprene  | C5 to C10 aldehydes  |
| "Urban grime"  | Polycyclic aromatic hydrocarbons   | Oxidized polycyclic aromatic hydrocarbons  |
| Perfumes, colognes, essential oils (e.g.<br>lavender, eucalyptus, tea tree)            | Limonene, alpha-pinene, linalool, linalyl acetate, terpinene-4-ol, gamma-terpinene   | Formaldehyde, 4-AMC, acetone, 4-hydroxy-<br>4-methyl-5-hexen-1-al, 5-ethenyl-dihydro-<br>5-methyl-2(3H) furanone, SOAs including<br>ultrafine particles  |
| Overall home emissions   | Limonene, alpha-pinene, styrene  | Formaldehyde, 4-AMC, pinonaldehyde,<br>acetone, pinic acid, pinonic acid, formic acid,<br>benzaldehyde, SOAs including ultrafine<br>particles  |

Abbreviations: 4-AMC, 4-acetyl-1-methylcyclohexene; 6MHQ, 6-methyl-5-heptene-2-one, 4OPA, 4-oxopentanal, SOA, Secondary Organic Aerosols

Reference: Charles J Weschler; Environmental Helath Perspectives, Vol 114, October 2006. DO NOT discharge into sewer or waterways.

**GESAMP/EHS COMPOSITE LIST - GESAMP Hazard Profiles** 

| Name /<br>Cas No /<br>RTECS No                         | EHS | TRN      | A1a     | A1b | A1  | A2       | B1 | B2  | C1 | C2   | C3 | D1  | D2  | D3       | E1  | E2     | E3 |
|--|-----|----------|---------|-----|-----|----------|----|-----|----|------|----|-----|-----|----------|-----|--------|----|
| E1:_INTER<br>F~ /<br>CAS:8001-<br>25- 0 /<br>RK4300000 |     | 109<br>0 | 27<br>1 | 7 — | 0 N | <u> </u> | R  | (2) | N  | II ( | 0) | (0) | (1) | <u> </u> | 1 1 | <br>Fp | 2  |

Legend: EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships) NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation, B1=Acuteaquatic toxicity LC/ECIC50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg), C2=Acutemammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion, D2=Eye irritation& corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference with coastal amenities, For column A2: R=Readily biodegradable, NR=Not readily biodegradable. For column D3: C=Carcinogen, M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lunginjury, N=Neurotoxic, I=Immunotoxic. For column E1: NT=Not tainting (tested), T=Tainting test positive. For column E2: Fp=Persistent floater, F=Floater, S=Sinking substances. The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard. (GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships)

# Section 13 - DISPOSAL CONSIDERATIONS

# **Disposal Instructions**

All waste must be handled in accordance with local, state and federal regulations.

| Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorized landfill.

# Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

# Section 15 - REGULATORY INFORMATION

#### REGULATIONS

#### olive oil (CAS: 8001-25-0,84012-27-1) is found on the following regulatory lists;

"Canada Domestic Substances List (DSL)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk Liquid Cargoes", "US Toxic Substances Control Act (TSCA) - Inventory"

# **Section 16 - OTHER INFORMATION**

#### LIMITED EVIDENCE

- Cumulative effects may result following exposure\*.
- May produce skin discomfort\*.
- \* (limited evidence).

#### Ingredients with multiple CAS Nos

Ingredient Name olive oil CAS 8001-25-0, 84012-27-1

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Nov-1-2007 Print Date:Aug-12-2010