

Dichloromethane

sc-239703

Material Safety Data Sheet



The Power is Question

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Dichloromethane

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Company: Santa Cruz Biotechnology, Inc.

Address:

2145 Delaware Ave
Santa Cruz, CA 95060

Telephone: 800.457.3801 or 831.457.3800

Emergency Tel: **CHEMWATCH: From within the US and Canada:**
877-715-9305

Emergency Tel: **From outside the US and Canada: +800 2436 2255**
(1-800-CHEMCALL) or call +613 9573 3112

PRODUCT USE

■ The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Solvent for cellulose acetate, plastics and fats. Component of degreasing agents, cleaning fluids and paint removers. A blowing agent in foams, as an aerosol propellant, and a cooling solvent.

SYNONYMS

C-H₂-Cl₂, dichloromethane, "methylene bichloride", "methylene dichloride", NCI-C50102, "methane dichloride", "Aerotherne MM", DCM, Solaesthin, Solmethine, Narkotil, "RCRA Waste Number U080", "R 30", "Restek Grob Test Mix", 24/R1325, "Product Code 270563"

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability:	0	
Toxicity:	2	
Body Contact:	2	
Reactivity:	1	
Chronic:	3	

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Harmful if swallowed.

Irritating to skin.

Limited evidence of a carcinogenic effect.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

EYE

■ There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.

SKIN

■ The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterized by redness, swelling and blistering.

■ Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

■ Open cuts, abraded or irritated skin should not be exposed to this material.

■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

■ Inhalation of vapors or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

■ There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

■ Inhalation hazard is increased at higher temperatures.

■ Inhalation exposure may cause susceptible individuals to show change in heart beat rhythm i.e. cardiac arrhythmia. Exposures must be terminated.

■ Acute intoxication by halogenated aliphatic hydrocarbons appears to take place over two stages. Signs of a reversible narcosis are evident in the first stage and in the second stage signs of injury to organs may become evident, a single organ alone is (almost) never involved.

CHRONIC HEALTH EFFECTS

■ There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

There is some evidence to provide a presumption that human exposure to the material may result in impaired fertility on the basis of: some evidence in animal studies of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects but which is not a secondary non-specific consequence of other toxic effects.

Dichloromethane exposures cause liver and kidney damage in animals and this justifies consideration before exposing persons with a history of impaired liver function and/or renal disorders.

Dichloromethane is stored in body fat and metabolized to carbon monoxide, which reduces the oxygen carrying capacity of blood.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
methylene chloride	75-09-2	> 99

Section 4 - FIRST AID MEASURES

SWALLOWED

■

● IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.

● Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

● For advice, contact a Poisons Information Center or a doctor.

- Urgent hospital treatment is likely to be needed.
- If conscious, give water to drink.
- INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
- If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist.
- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.
- Avoid giving milk or oils.
- Avoid giving alcohol.

EYE

- If this product comes in contact with the eyes:
 - Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
 - Lay patient down. Keep warm and rested.
 - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
 - Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- For acute or short term repeated exposures to methylene chloride:
 - Methylene chloride is well absorbed by the lung. An 8 hour exposure to 250 ppm causes carboxyhemoglobin levels to exceed 8%. Physical exertion and smoke produce an additive effect.
 - The lungs exhale most of the absorbed dose unchanged. Between 1/4 and 1/3 is metabolized to carbon monoxide / dioxide. 5 hours of 100% oxygen is required, typically, to reduce the carboxyhemoglobin level from 13% to 7.5%.
 - As with inhalation and ingestion of the hydrocarbons support of respiration and monitoring for dysrhythmias are the first steps toward stabilization.
 - Small ingestions require only dilution with water or milk. Patients who have ingested more than several swallows may benefit from Ipecac Syrup/lavage, charcoal or cathartics. No data is available to support the efficacy of these treatments.

[Ellenhorn and Barceloux: Medical Toxicology]BIOLOGICAL EXPOSURE INDEX - BEI

Determinant	Index	Sampling Time	Comments
1. Methemoglobin in blood	1.5% of hemoglobin	During or end of shift	B, NS, SQ

B: Background levels occur in specimens collected from subjects NOT exposed.

NS: Non-specific determinant; Also seen after exposure to other materials

SQ: Semi-quantitative determinant - Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

Section 5 - FIRE FIGHTING MEASURES

Vapor Pressure (mmHg):	348.779 @20C
Upper Explosive Limit (%):	22-oxygen rich
Specific Gravity (water=1):	1.32
Lower Explosive Limit (%):	14-oxygen rich

EXTINGUISHING MEDIA

- - Water spray or fog.
 - Foam.
 - Dry chemical powder.
 - BCF (where regulations permit).
 - Carbon dioxide.

FIRE FIGHTING

- - Alert Emergency Responders and tell them location and nature of hazard.

- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

■ Decomposes on heating and produces acrid and toxic fumes of: carbon dioxide (CO₂), hydrogen chloride, phosgene, other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

May emit poisonous fumes.

- Non flammable liquid.
- However vapor will burn when in contact with high temperature flame.
- Ignition ceases on removal of flame.
- May form a flammable / explosive mixture in an oxygen enriched atmosphere
- Heating may cause expansion/vaporization with violent rupture of containers
- Decomposes on heating and produces corrosive fumes of hydrochloric acid, carbon monoxide and small amounts of toxic phosgene.

FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:

Safety Glasses.

Chemical goggles.

Gloves:

1. PE/EVAL/PE 2. PVA 3. TEFLON

Respirator:

Type AX Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

-
- Clean up all spills immediately.
- Avoid breathing vapors and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labeled container for waste disposal.

MAJOR SPILLS

■ Chemical Class: aliphatics, halogenated

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
cross-linked polymer - particulate	1	shovel	shovel	R, W, SS
cross-linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
wood fiber - pillow	2	throw	pitchfork	R, P, DGC, RT
treated wood fibre - particulate	2	shovel	shovel	R, W, DGC
sorbent clay - particulate	3	shovel	shovel	R, I, P
foamed glass - pillow	3	throw	pitchfork	R, P, DGC, RT
LAND SPILL - MEDIUM				
cross-linked polymer - particulate	1	blower	skid loader	R, W, SS
cross-linked polymer - pillow	2	throw	skid loader	R, DGC, RT
sorbent clay - particulate	3	blower	skid loader	R, I, P
polypropylene - particulate	3	blower	skid loader	W, SS, DGC
foamed glass - pillow	3	throw	skid loader	R, P, DGC, RT
expanded mineral - particulate	4	blower	skid loader	R, I, W, P, DGC

Legend

DGC: Not effective where ground cover is dense

R: Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

life-threatening health effects is:

methylene chloride 4000ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

methylene chloride 750ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

methylene chloride 200ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according exceed the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

■ Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers.
- Vent periodically
- Always release caps or seals slowly to ensure slow dissipation of vapors
- DO NOT allow clothing wet with material to stay in contact with skin

RECOMMENDED STORAGE METHODS

■ DO NOT use aluminum or galvanized containers.

- Lined metal can, Lined metal pail/drum
- Plastic pail
- Polyliner drum
- Packing as recommended by manufacturer.
- Check all containers are clearly labeled and free from leaks.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging;
- Cans with friction closures and
- low pressure tubes and cartridges may be used.

- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages * . - In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *. - * unless the outer packaging is a close fitting molded plastic box and the substances are not incompatible with the plastic.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)	methylene chloride (METHYLENE CHLORIDE)	0.6							
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)	methylene chloride (METHYLENE CHLORIDE)	0.3							
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)	methylene chloride (METHYLENE CHLORIDE)	0.3							
Canada - Alberta Occupational Exposure Limits	methylene chloride (Methylene chloride (Dichloromethane))	50	174						
Canada - Alberta Occupational Exposure Limits	methylene chloride (Dichloromethane (Methylene chloride))	50	174						
Canada - Ontario Occupational Exposure Limits	methylene chloride (Dichloromethane)	50	175						
Canada - British Columbia Occupational Exposure Limits	methylene chloride (Dichloromethane)	25							2B
US - Idaho - Acceptable Maximum Peak Concentrations	methylene chloride (Methylene chloride (Z37.23-1969))	500				1,000			
US - Idaho - Limits for Air Contaminants	methylene chloride (Methylene chloride)		[2]						
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	methylene chloride (Methylene chloride)	500				1,000			
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	methylene chloride (Methylene chloride)		See Table Z-2						
US - California Permissible Exposure Limits for Chemical Contaminants	methylene chloride (Methylene chloride; dichloromethane (see also section 5202))	25	87	125	435				
US ACGIH Threshold Limit Values (TLV)	methylene chloride (Dichloromethane)	50							TLV Basis: carboxyhemoglobinemia; central nervous system impairment. BEI
US - Hawaii Air Contaminant Limits	methylene chloride (Methylene chloride)	25							See °12-202-41
US - Oregon Permissible Exposure Limits (Z-1)	methylene chloride (Methylene Chloride)	25							TWA (See 1910.1052)
US - Michigan Exposure Limits for Air Contaminants	methylene chloride (Methylene chloride, see R 325.51651 et seq.F)	25	87	125	434				
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	methylene chloride (Methylene chloride (dichloromethane))	200	700	250	870				
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	methylene chloride (Dichloromethane, see Methylene chloride)	200	720	200	720				

US - Washington Permissible exposure limits of air contaminants	methylene chloride (Dichloromethane (Methylene chloride) (See chapter 296-859 WAC))	25	125		
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	methylene chloride (Methylene chloride (dichloromethane))	50	63		
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	methylene chloride (Dichloromethane)	50	75		T20
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	methylene chloride (Methylene chloride)	50	174		
US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	methylene chloride (Methylene Chloride: see 1910.1052)	25	125		
Canada - Northwest Territories Occupational Exposure Limits (English)	methylene chloride (Methylene chloride (Dichloromethane))	100	347	500	1737
Canada - Northwest Territories Occupational Exposure Limits (English)	methylene chloride (Dichloromethane (Methylene chloride))	100	347	500	1737
Canada - Nova Scotia Occupational Exposure Limits	methylene chloride (Dichloromethane)	50			TLV Basis: carboxyhemoglobinemia; central nervous system impairment. BEI
Canada - Prince Edward Island Occupational Exposure Limits	methylene chloride (Dichloromethane)	50			TLV Basis: carboxyhemoglobinemia; central nervous system impairment. BEI
US TSCA New Chemical Exposure Limits (NCEL)	methylene chloride (Halogenated alkanes (P84-106/107))	1.0			

EMERGENCY EXPOSURE LIMITS

Material	methylene chloride
----------	--------------------

Original IDLH Value (ppm)

MATERIAL DATA

METHYLENE CHLORIDE:

■ For methylene chloride

Odour Threshold Value: 158 ppm (detection), 227 ppm (recognition)

NOTE: Detector tubes for methylene chloride, measuring in excess of 25 ppm are commercially available. Long-term measurements (4 hrs) may be conducted to detect concentrations exceeding 13 ppm.

Exposure at or below the recommended TLV-TWA (and in the absence of occupational exposure to carbon monoxide) is thought to minimise the potential for liver injury and to provide protection against the possible weak carcinogenic effects which have been demonstrated in laboratory rats and mice. Enhancement of tumours of the lung, liver, salivary glands and mammary tissue in rodent studies has lead NIOSH to recommend a more conservative outcome. The ACGIH however concludes that in the absence of documentation of health-related injuries at higher exposures after a long history of methylene chloride use and a number of epidemiologic studies, the recommended TLV-TWA provides an adequate margin of safety.

Concentration effects:

Concentration	Clinical effects
>300 ppm	Sweet odour
500-1000 ppm (1-2 h)	Unpleasant odour, slight anaesthetic effects, headache, light-headedness, eye irritation and elevated COHb concentration
2300 ppm (5 min.)	Odour strong, intensely irritating; dizziness
7200 ppm (8-16 min)	Paraesthesia, tachycardia

>50000 ppm

Immediately life-threatening

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

PERSONAL PROTECTION



Consult your EHS staff for recommendations

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

OTHER

- Overalls.
- Eyewash unit.
- Barrier cream.
- Skin cleansing cream.

GLOVE SELECTION INDEX

- Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection: methylene chloride

- Protective Material CPI *

PE/EVAL/PE	A
PVA	A
TEFLON	B
VITON	C
VITON/BUTYL	C
VITON/CHLOROBUTYL	C
CPE	C
BUTYL	C
NATURAL RUBBER	C
NEOPRENE	C

- * CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half-face Respirator	Full-Face Respirator
1000	10	AX-1	-
1000	50	-	AX-1
5000	50	Airline*	-
5000	100	-	AX-2
10000	100	-	AX-3
	100+		Airline* *

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

ENGINEERING CONTROLS

■ Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator. Correct fit is essential to obtain adequate protection an approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapors, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favorable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Liquid.

State	Liquid	Molecular Weight	84.93
Melting Range (°F)	-142.6	Viscosity	Not Available
Boiling Range (°F)	104	Solubility in water (g/L)	2.0%

Flash Point (°F)	Not applicable	pH (1% solution)	Not applicable.
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	1223.6	Vapor Pressure (mmHg)	348.779 @20C
Upper Explosive Limit (%)	22-oxygen rich	Specific Gravity (water=1)	1.32
Lower Explosive Limit (%)	14-oxygen rich	Relative Vapor Density (air=1)	2.93
Volatile Component (%vol)	100	Evaporation Rate	>1 BuAc=1
Gas group	IIA		

METHYLENE CHLORIDE

■ log Kow (Prager 1995): 1.25

APPEARANCE

Colourless non flammable liquid; does not mix with water. Highly volatile. Has a penetrating, ether-like odour. Mixes with alcohol, organic solvents.

log Kow 1.25

Material	Value
■ log Kow (Prager 1995)	1.25

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

-
- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

STORAGE INCOMPATIBILITY

- Methylene chloride
 - is a combustible liquid under certain circumstances even though there is no measurable flash point and it is difficult to ignite
 - its is flammable in ambient air in the range 12-23%; increased oxygen content can greatly enhance fire and explosion potential
 - contact with hot surfaces and elevated temperatures can form fumes of hydrogen chloride and phosgene
 - reacts violently with active metals, aluminium, lithium, methanol,, peroxydisulfuryl difluoride, potassium, potassium tert-butoxide, sodium
 - forms explosive mixtures with nitric acid
 - is incompatible with strong oxidisers, strong caustics, alkaline earths and alkali metals
 - attacks some plastics, coatings and rubber
 - may generate electrostatic charge due to low conductivity

Segregate from:

- powdered metals such as aluminium, zinc and
- alkali metals such as sodium, potassium and lithium.

May attack, soften or dissolve rubber, many plastics, paints and coatings.

Segregate from alcohol, water.

Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

METHYLENE CHLORIDE

TOXICITY AND IRRITATION

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY	IRRITATION
Oral (human) LDLo: 357 mg/kg	Skin (rabbit): 810 mg/24hr-SEVERE
Oral (rat) LD50: 1600 mg/kg	Skin (rabbit): 100mg/24hr-Moderate
Inhalation (human) TCLo: 500 ppm/ 8 hr	Eye(rabbit): 162 mg - Moderate
Inhalation (rat) LC50: 88000 mg/m ³ /30 m	Eye(rabbit): 500 mg/24hr - Mild

■ The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Inhalation (human) TCLo: 500 ppm/ 1 y - I Eye(rabbit): 10 mg - mild

CARCINOGEN

Dichloromethane (methylene chloride)	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	2B
Dichloromethane	ND	Carcinogenicity	B2
Dichloromethane	ND	Carcinogen Category	B2
Dichloromethane	ND	Carcinogen Category	A3
DICHLOROMETHANE	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65
DICHLOROMETHANE	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65
Methylene chloride	US Air Toxics Hot Spots TSD for Describing Available Cancer Potency Factors	IARC Class	2B
Dichloromethane	ND	Carcinogen	Ca

REPROTOXIN

methylene chloride	ILO Chemicals in the electronics industry that have toxic effects on reproduction	Reduced fertility or sterility
--------------------	---	--------------------------------

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

METHYLENE CHLORIDE:

■ Fish LC50 (96hr.) (mg/l):	147.6- 193
■ Daphnia magna EC50 (48hr.) (mg/l):	224
■ BCF<100:	5
■ log Kow (Prager 1995):	1.25
■ Half- life Soil - High (hours):	672
■ Half- life Soil - Low (hours):	168
■ Half- life Air - High (hours):	4584
■ Half- life Air - Low (hours):	458
■ Half- life Surface water - High (hours):	672
■ Half- life Surface water - Low (hours):	168
■ Half- life Ground water - High (hours):	1344
■ Half- life Ground water - Low (hours):	336
■ Aqueous biodegradation - Aerobic - High (hours):	672
■ Aqueous biodegradation - Aerobic - Low (hours):	168
■ Aqueous biodegradation - Anaerobic - High (hours):	2688
■ Aqueous biodegradation - Anaerobic - Low (hours):	672
■ Aqueous biodegradation - Removal secondary treatment - High (hours):	94.50%
■ Photolysis maximum light absorption - High (nano- m):	250
■ Photolysis maximum light absorption - Low (nano- m):	220
■ Photooxidation half- life air - High (hours):	4584
■ Photooxidation half- life air - Low (hours):	458
■ First order hydrolysis half- life (hours):	704 YR

■ For methylene chloride:

log Kow: 1.25

log Koc: 1.68

log Kom: 1.44

Henry's atm m³ /mol: 2.68E-03

BCF: 5

Environmental fate:

Methylene chloride is a volatile liquid, and tends to volatilise to the atmosphere from water and soil. The half-life of methylene chloride volatilisation from water has been found to be 21 minutes under experimental conditions but actual volatilisation from natural waters will depend on the rate of mixing, wind speed, temperature, and other factors. The Henry's law constant value (H) of 0.002 atm/m³/mol indicates that methylene chloride will volatilise rapidly from moist soil and water surfaces.

Methylene chloride is not strongly sorbed to soils or sediments. Based on its low soil organic carbon partitioning coefficient (Koc) of 25, methylene chloride is likely to be very highly mobile in soils and may be expected to leach from soils into groundwater.

Based on a reported log octanol/water partition coefficient (Kow) of 1.3 an estimated bioconcentration factor (BCF) of 2.3 was derived. There is no evidence of biomagnification, but because the estimated BCF is low, significant biomagnification of methylene chloride in aquatic food chains is not expected.

Air: The main degradation pathway for methylene chloride in air is its reaction with photochemically generated hydroxyl radicals. Thus, the atmospheric lifetime of methylene chloride may be predicted from the hydroxyl radical concentration in air and the rate of reaction. Most reported rates for hydroxyl radical reaction with methylene chloride range from 1.0×10^{-13} to 1.5×10^{-13} cm³/mol/sec, and estimates of average atmospheric hydroxyl radical concentration range from 2.5×10^5 to 1×10^6 mol/cm³. Using this information, an average atmospheric lifetime for methylene chloride may be calculated to be 130 days. Because this degradation pathway is relatively slow, methylene chloride may become widely dispersed but is not likely to accumulate in the atmosphere. The small amount of methylene chloride which reaches the stratosphere (about 1%) may undergo direct photolytic degradation; however, photolysis in the troposphere is not expected. Reactions of methylene chloride with ozone or other common atmospheric species (e.g., oxygen atoms, chlorine atoms, and nitrate radicals) are not believed to contribute to its breakdown.

Water: Methylene chloride undergoes slow hydrolysis in water. The experimental half-life reported for the hydrolysis reaction, at neutral conditions, is approximately 18 months at 25 C.

However, the rate of reaction varies greatly with changes in temperature and pH. A hydrolytic half-life of 14 days was reported for methylene chloride in acidic solutions at 80-150 C. This experimental value, when extrapolated to 25 C, is about 700 years. Different mechanisms of hydrolyses may be responsible for these two widely different values.

Both aerobic and anaerobic biodegradation may be an important fate process for methylene chloride in water. Methylene chloride has been observed to undergo degradation at a rapid rate under aerobic conditions. Reported total methylene chloride loss was 100% after 7 days in a static culture flask biodegradability screening test.

Sediment and Soil: The rate of biodegradation was found to be dependent on soil type, substrate concentration, and redox state of the soil. Methylene chloride biodegradation has been reported to occur under both aerobic conditions and anaerobic conditions. The biodegradation of methylene chloride appears to be accelerated by the presence of elevated levels of organic carbon.

Methylene chloride has a low tendency to absorb to soil; therefore, there is a potential for leaching to groundwater. Also, because of the high vapor pressure, volatilisation to air is also a likely fate process from dry soil. Its high Henry's law constant (0.002 atm/m³/mol) indicates that volatilization from moist soil is also likely.

■ The UK Department of Environment have established that methylene chloride is not a greenhouse gas and the Organisation for Economic Cooperation and Development (OECD) in a Monograph have affirmed that there was no single international view that risk reduction measures are required for the solvent. The Monograph suggests that alternatives may pose a greater risk to the environment.

In the atmosphere methylene chloride degrades by reaction with photochemically produced hydroxy radicals (half-life 6 months). Methylene chloride rapidly volatilises from water and soil to the atmosphere (estimated half-life for volatilisation from water 3-5.6 hours). In soil methylene chloride may partially leach to ground water. It is not expected to bioaccumulate or bioconcentrate in the food chain.

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max)

dichloromethane: 20 ug/l (WHO guideline)

Soil Guidelines: Dutch Criteria: detection threshold (target)

20 mg/kg (intervention)

Air Quality Standards:

3 mg/m³ averaging time 24 hours (WHO guideline).

■ DO NOT discharge into sewer or waterways.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
methylene chloride	LOW	HIGH	LOW	HIGH

GESAMP/EHS COMPOSITE LIST - GESAMP Hazard Profiles

Name / Cas No / RTECS No	EHS	TRN	A1a	A1b	A1	A2	B1	B2	C1	C2	C3	D1	D2	D3	E1	E2	E3	
E2~ / CAS:75- 09- 2 / PA8050000	—	—	594	234	1	2	2	NR	1	0	1	0	0	2	2	C	SD	3

Legend: EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships)
 NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation,
 B1=Acuteaquatic toxicity LC/ECIC50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg),
 C2=Acute mammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion,
 D2=Eye irritation & corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference
 with coastal amenities, For column A2: R=Readily biodegradable, NR=Not readily biodegradable. For column D3: C=Carcinogen,
 M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lunginjury, N=Neurotoxic,
 I=Immunotoxic. For column E1: NT=Not tainting (tested), T=Tainting test positive. For column E2: Fp=Persistent floater, F=Floater, S=Sinking
 substances. The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard. (GESAMP/EHS Composite List
 of Hazard Profiles - Hazard evaluation of substances transported by ships)

Section 13 - DISPOSAL CONSIDERATIONS

US EPA Waste Number & Descriptions

B. Component Waste Numbers

When methylene chloride is present as a solid waste as a discarded commercial chemical product, off-specification species, as a container residue, or a spill residue, use EPA waste number U080 (waste code T).

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in

their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorized landfill.

Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols:	None	Hazard class or Division:	6.1
Identification Numbers:	UN1593	PG:	III
Label Codes:	6.1	Special provisions:	IB3, IP8, N36, T7, TP2
Packaging: Exceptions:	153	Packaging: Non-bulk:	203
Packaging: Exceptions:	153	Quantity limitations: Passenger aircraft/rail:	60 L
Quantity Limitations: Cargo aircraft only:	220 L	Vessel stowage: Location:	A
Vessel stowage: Other:	None		

Hazardous materials descriptions and proper shipping names:

Dichloromethane

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1593	Packing Group:	III
Special provisions:	None		

Shipping Name: DICHLOROMETHANE

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
UN Number:	1593	Packing Group:	III
EMS Number:	F-A, S-A	Special provisions:	None

Limited Quantities: 5 L

Shipping Name: DICHLOROMETHANE

Section 15 - REGULATORY INFORMATION



REGULATIONS

methylene chloride (CAS: 75-09-2) is found on the following regulatory lists;

"Canada - Alberta Occupational Exposure Limits", "Canada - British Columbia Occupational Exposure Limits", "Canada - Northwest Territories Occupational Exposure Limits (English)", "Canada - Nova Scotia Occupational Exposure Limits", "Canada - Ontario Occupational Exposure

Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens", "Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)", "Canada - Saskatchewan Environmental Persistent or Chronic Hazardous Substances", "Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits", "Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances", "Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances", "Canada ARET (Accelerated Reduction / Elimination of Toxics) Substance List", "Canada Domestic Substances List (DSL)", "Canada Environmental Protection Act (CEPA) 1999 - Schedule 1 Toxic Substances List", "Canada Environmental Quality Guidelines (EQGs) Water: Aquatic life", "Canada Environmental Quality Guidelines (EQGs) Water: Community", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada National Pollutant Release Inventory (NPRI)", "Canada Priority Substances List (PSL1, PSL 2)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - Alaska Limits for Air Contaminants", "US - California Air Toxics ""Hot Spots"" List (Assembly Bill 2588) Substances for which emissions must be quantified", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - Carcinogens", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - California Toxic Air Contaminant List Category II", "US - Connecticut Hazardous Air Pollutants", "US - Hawaii Air Contaminant Limits", "US - Idaho - Acceptable Maximum Peak Concentrations", "US - Idaho - Limits for Air Contaminants", "US - Maine Chemicals of High Concern List", "US - Massachusetts Oil & Hazardous Material List", "US - Michigan Exposure Limits for Air Contaminants", "US - Minnesota Hazardous Substance List", "US - Minnesota Permissible Exposure Limits (PELs)", "US - New Jersey Right to Know Hazardous Substances", "US - Oregon Hazardous Materials", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Pennsylvania - Hazardous Substance List", "US - Rhode Island Hazardous Substance List", "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Hazardous Constituents", "US - Vermont Hazardous wastes which are Discarded Commercial Chemical Products or Off-Specification Batches of Commercial Chemical Products or Spill Residues of Either", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Class A toxic air pollutants: Known and Probable Carcinogens", "US - Washington Dangerous waste constituents list", "US - Washington Discarded Chemical Products List - ""U"" Chemical Products", "US - Washington Permissible exposure limits of air contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift", "US ACGIH Threshold Limit Values (TLV)", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)", "US CAA (Clean Air Act) - HON Rule - Organic HAPs (Hazardous Air Pollutants)", "US CERCLA Priority List of Hazardous Substances", "US Clean Air Act - Hazardous Air Pollutants", "US Cosmetic Ingredient Review (CIR) Cosmetic ingredients found safe, with qualifications", "US CWA (Clean Water Act) - Priority Pollutants", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA Acute Exposure Guideline Levels (AEGLs) - Interim", "US EPA Carcinogens Listing", "US EPA High Production Volume Program Chemical List", "US EPA Master Testing List - Index I Chemicals Listed", "US EPA National Priorities List - Superfund Chemical Data Matrix (SCDM) - Hazard Ranking System - Hazardous Substance Benchmarks", "US EPCRA Section 313 Chemical List", "US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives", "US Food Additive Database", "US List of Lists - Consolidated List of Chemicals Subject to the Emergency Planning and Community Right-to-Know Act (EPCRA) and Section 112(r) of the Clean Air Act", "US National Toxicology Program (NTP) 11th Report Part B. Reasonably Anticipated to be a Human Carcinogen", "US NFPA 30B Manufacture and Storage of Aerosol Products - Chemical Heat of Combustion", "US NIOSH Recommended Exposure Limits (RELs)", "US OSHA Carcinogens Listing", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US OSHA Permissible Exposure Levels (PELs) - Table Z2", "US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide", "US RCRA (Resource Conservation & Recovery Act) - Appendix IX to Part 264 Ground-Water Monitoring List 1", "US RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261", "US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Inorganic and Organic Constituents 1", "US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Wastes", "US RCRA (Resource Conservation & Recovery Act) - Phase 4 LDR Rule - Universal Treatment Standards", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US Toxic Substances Control Act (TSCA) - Inventory", "US TSCA Section 8 (d) - Health and Safety Data Reporting", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

Section 16 - OTHER INFORMATION

LIMITED EVIDENCE

- Inhalation and/or skin contact may produce health damage*.
- Cumulative effects may result following exposure*.
- May produce discomfort of the eyes and respiratory tract*.
- May affect fertility*.
- Repeated exposure potentially causes skin dryness and cracking*.
- Vapors potentially cause drowsiness and dizziness*.

* (limited evidence).

REPRODUCTIVE HEALTH GUIDELINES

- Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
methylene chloride	2.4 mg/m3	100	R	14	-

- These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally

safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise. CR = Cancer Risk/10000; UF = Uncertainty factor: TLV believed to be adequate to protect reproductive health: LOD: Limit of detection Toxic endpoints have also been identified as: D = Developmental; R = Reproductive; TC = Transplacental carcinogen Jankovic J., Drake F.: A Screening Method for Occupational Reproductive Health Risk: American Industrial Hygiene Association Journal 57: 641-649 (1996).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

■ Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Aug-4-2009

Print Date: Aug-11-2010