# S(-)-Propranolol • HCI

# sc-200153

**Material Safety Data Sheet** 



The Power to Oscotion

Hazard Alert Code Key: EXTREME HIGH MODERATE LOW

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

## **PRODUCT NAME**

S(-)-Propranolol • HCI

#### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

## **NFPA**



## **SUPPLIER**

Santa Cruz Biotechnology, Inc. 2145 Delaware Avenue Santa Cruz, California 95060 800.457.3801 or 831.457.3800

# **EMERGENCY** ChemWatch


Within the US & Canada: 877–715–9305 Outside the US & Canada: +800 2436 2255 (1–800-CHEMCALL) or call +613 9573 3112

## **SYNONYMS**

C16H21NO2 • HCI, "2-propanol, 1-(isopropylamino)-3-(1-napthyloxy)-2-propanol hydrochloride", "DL-propranolol hydrochloride", "propanolol hydrochloride (sic)", Angilol, Apsolol, Berkolol, Inderal, Inderetic, Blocardyl, Noloten, Oposim, Propayerst, Cardinol, Frekven, Avlocardyl, Betaryl, Dociton, Beta-Neg, Tonum, Caridolol, Herzul, Kemi, Pylapron, Tesnol, Pranolol, Pronovan, Sumial, "beta-adrenoreceptor blocker"

## **Section 2 - HAZARDS IDENTIFICATION**

## **CHEMWATCH HAZARD RATINGS**



## **CANADIAN WHMIS SYMBOLS**





## **EMERGENCY OVERVIEW**

#### RISK

May cause SENSITISATION by skin contact. Harmful by inhalation, in contact with skin and if swallowed.

#### POTENTIAL HEALTH EFFECTS

#### **ACUTE HEALTH EFFECTS**

#### **SWALLOWED**

- Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
- Side effects from beta-locking agents include nausea, vomiting, disturbance of of the gastrointestinal tract, fatigue and dizziness.

The nervous system may be involved, causing depression, delirium, stoppage of breathing, confusion, psychosis, motor abnormalities, coma, visual disturbance and insomnia.

#### **EYE**

■ Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn).

Slight abrasive damage may also result.

■ Eye absorption of beta blockers can reduce the pressure in the eye and causesystemic toxicity.

#### SKIN

- Skin contact with the material may be harmful; systemic effects may resultfollowing absorption.
- The material is not thought to be a skin irritant (as classified using animal models).

Abrasive damage however, may result from prolonged exposures.

- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

#### **INHALED**

- Inhalation of dusts, generated by the material, during the course of normalhandling, may be harmful.
- The material is not thought to produce respiratory irritation (as classified using animal models).

Nevertheless inhalation of dusts, or fume, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

■ Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

## **CHRONIC HEALTH EFFECTS**

■ Skin contact with the material is more likely to cause a sensitization reaction in some persons compared to the general population. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

Prolonged use of beta blockers can result in dry mouth, taste distortion, heartburn, stomach pain, nausea, vomiting, loss of appetite, bloating, flatulence, and diarrhea or constipation. The nervous system may be affected by fatigue, headache, dizziness, lethargy, depression, "pins and needles", reduced or increased sensation, anxiety, nervousness, poor concentration, sleep loss and nightmares or bizarre dreams.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
propranolol hydrochloride	4199-10-4	>98

## **Section 4 - FIRST AID MEASURES**

## **SWALLOWED**

· IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. · Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

#### **EYE**

■ If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

#### SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

#### **INHALED**

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

#### **NOTES TO PHYSICIAN**

■ Following a recent overdosage with a beta-blocker the stomach should be emptied by gastric lavage. Emesis should not be used.

Almost completely absorbed from the gastrointestinal tract and subject to first pass metabolism. Excreted in the urine mainly as metabolites. Crosses the placenta and blood-brain barrier. Highly protein-bound.

Section 5 - FIRE FIGHTING MEASURES				
Vapour Pressure (mmHG):	Negligible			
Upper Explosive Limit (%):	Not available			
Specific Gravity (water=1):	Not available			
Lower Explosive Limit (%):	Not available			

#### **EXTINGUISHING MEDIA**

- · Water spray or fog.
- · Foam.

#### **FIRE FIGHTING**

- · Alert Emergency Responders and tell them location and nature of hazard.
- · Wear breathing apparatus plus protective gloves.

#### **GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS**

- · Combustible solid which burns but propagates flame with difficulty.
- · Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO2), hydrogen chloride, phosgene, nitrogen oxides (NOx), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

#### FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## **PERSONAL PROTECTION**

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

# Section 6 - ACCIDENTAL RELEASE MEASURES

## MINOR SPILLS

- · Clean up waste regularly and abnormal spills immediately.
- · Avoid breathing dust and contact with skin and eyes.
- · Wear protective clothing, gloves, safety glasses and dust respirator.
- · Use dry clean up procedures and avoid generating dust.
- · Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).
- Dampen with water to prevent dusting before sweeping.
- · Place in suitable containers for disposal.

MAJOR SPILLS

#### ■ Moderate hazard.

- · CAUTION: Advise personnel in area.
- $\cdot$  Alert Emergency Responders and tell them location and nature of hazard.

## **Section 7 - HANDLING AND STORAGE**

## PROCEDURE FOR HANDLING

- $\cdot$  Avoid all personal contact, including inhalation.
- · Wear protective clothing when risk of exposure occurs.

Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.

- · Do NOT cut, drill, grind or weld such containers.
- · In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

## **RECOMMENDED STORAGE METHODS**

- Glass container.
- · Polyethylene or polypropylene container.

· Check all containers are clearly labelled and free from leaks.

#### STORAGE REQUIREMENTS

- · Store in original containers.
- · Keep containers securely sealed.

NOTE: Store in the dark.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## **EXPOSURE CONTROLS**

The following materials had no OELs on our records

• propranolol hydrochloride: CAS:3506-09-0 CAS:318-98-9 CAS:13071-11-9 CAS:4199-10-4

#### PERSONAL PROTECTION



#### **RESPIRATOR**

Particulate

Consult your EHS staff for recommendations

#### FYF

■ When handling very small quantities of the material eye protection may not be required.

For laboratory, larger scale or bulk handling or where regular exposure in an occupational setting occurs:

- · Chemical goggles
- · Face shield. Full face shield may be required for supplementary but never for primary protection of eyes
- · Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

#### HANDS/FEET

■ NOTE: The material may produce skin sensitization in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- · frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- · dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- · Rubber gloves (nitrile or low-protein, powder-free latex). Employees allergic to latex gloves should use nitrile gloves in preference.
- · Double gloving should be considered.
- · PVC gloves.
- · Protective shoe covers.
- · Head covering.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- · polychloroprene
- nitrile rubber
- · butyl rubber
- · fluorocaoutchouc
- · polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

#### OTHER

- · For quantities up to 500 grams a laboratory coat may be suitable.
- · For quantities up to 1 kilogram a disposable laboratory coat or coverall of low permeability is recommended. Coveralls should be buttoned at collar and cuffs.
- · For quantities over 1 kilogram and manufacturing operations, wear disposable coverall of low permeability and disposable shoe covers.
- For manufacturing operations, air-supplied full body suits may be required for the provision of advanced respiratory protection.

- · Eye wash unit.
- · Ensure there is ready access to an emergency shower.
- · For Emergencies: Vinyl suit.

#### **ENGINEERING CONTROLS**

■ Enclosed local exhaust ventilation is required at points of dust, fume or vapor generation.

HEPA terminated local exhaust ventilation should be considered at point of generation of dust, fumes or vapors.

## **Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

#### PHYSICAL PROPERTIES

Solid

Mixes with water.

State	Divided solid	Molecular Weight	295.8
Melting Range (°F)	325- 329	Viscosity	Not Applicable
Boiling Range (°F)	Not applicable	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not available	pH (1% solution)	5-6
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not available	Specific Gravity (water=1)	Not available
Lower Explosive Limit (%)	Not available	Relative Vapor Density (air=1)	Not Applicable
Volatile Component (%vol)	Negligible	Evaporation Rate	Not Applicable

#### **APPEARANCE**

White, odourless, crystalline powder with bitter taste; mixes with water (1:20).

## **Section 10 - CHEMICAL STABILITY**

#### CONDITIONS CONTRIBUTING TO INSTABILITY

- · Presence of incompatible materials.
- · Product is considered stable.

## STORAGE INCOMPATIBILITY

■ Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

## **Section 11 - TOXICOLOGICAL INFORMATION**

propranolol hydrochloride

#### **TOXICITY AND IRRITATION**

PROPRANOLOL HYDROCHLORIDE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY IRRITATION
Oral (mouse) LD50: 380 mg/kg Nil Reported
Intraperitoneal (mouse) LD50: 87.6 mg/kg
Intravenous (mouse) LD50: 33.3 mg/kg
Intravenous (Human) TDLo: 0.1 mg/kg

Oral (Human) TDLo: 160 mg/kg Oral (Rat) LD50: 466 mg/kg

Intraperitoneal (Rat) LD50: 76 mg/kg Subcutaneous (Rat) LD50: 115 mg/kg

Oral (Human) LD: 64 mg/kg Oral (Human) LD: 34 mg/kg Oral (Human) TDLo: 417 mg/kg

Intravenous (Human) LD: 0.04 mg/kg

Oral (Mouse) LD50: 320 mg/kg

Intraperitoneal (Mouse) LD50: 80 mg/kg

Subcutaneous (Mouse) LD50: 208 mg/kg

Intravenous (Mouse) LD50: 18 mg/kg
Intravenous (Dog) LD: 22.811 mg/kg
Intravenous (Guinea pig) TDLo: 1 mg/kg
Oral (Rabbit) LD50: 600 mg/kg
Intravenous (Rabbit) LD50: 12.5 mg/kg
Intravenous (Guinea pig) LD: 28.1 mg/kg
Intraperitoneal (Rat) TDLo: 0.5 mg/kg

Intravenous (Rat) LD50: 40 mg/kg

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's edema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Effects on embryo, effects on newborn recorded.

#### **CARCINOGEN**

VPVB\_(VERY~ US - Maine Chemicals of High Concern List Carcinogen CA Prop 65; IARC; NTP 11th ROC

## Section 12 - ECOLOGICAL INFORMATION

No data

#### **Ecotoxicity**

Ingredient Persistence: Water/Soil Persistence: Air Bioaccumulation Mobility propranolol hydrochloride HIGH LOW MED

## **Section 13 - DISPOSAL CONSIDERATIONS**

#### **Disposal Instructions**

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- · Reuse
- Recycling
- · Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- · Recycle wherever possible.
- · Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

## **Section 14 - TRANSPORTATION INFORMATION**

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

#### Section 15 - REGULATORY INFORMATION

propranolol hydrochloride (CAS: 3506-09-0,318-98-9,13071-11-9,4199-10-4) is found on the following regulatory lists;

"OECD Representative List of High Production Volume (HPV) Chemicals"

## **Section 16 - OTHER INFORMATION**

#### ND

Substance CAS Suggested codes propranolol hydrochloride 3506- 09- 0 Xn; R22 propranolol hydrochloride 318- 98- 9 Mut3; R68 Xn; R22 R43 propranolol hydrochloride 13071- 11- 9 Xn; R22 propranolol hydrochloride 4199- 10- 4 Xn; R22

## Ingredients with multiple CAS Nos

Ingredient Name CAS propranolol hydrochloride 3506-09-0, 318-98-9, 13071-11-9, 4199-10-4

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

  A list of reference resources used to assist the committee may be found at:

  www.chemwatch.net/references.
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Feb-10-2009 Print Date:Mar-10-2011