

Citalopram

sc-201123



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Citalopram

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Santa Cruz Biotechnology, Inc.
2145 Delaware Avenue
Santa Cruz, California 95060
800.457.3801 or 831.457.3800

EMERGENCY

ChemWatch
Within the US & Canada: 877-715-9305
Outside the US & Canada: +800 2436 2255
(1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

C20-H21-NF-N2-O, "1-[3-(dimethylamino)propyl]-1-(4-fluorophenyl)-1,3-dihydro-5H-isobenzofuran-carbonitrile, 1-[3-(dimethylamino)propyl]-1-(4-fluorophenyl)-5-phthalanarbonitrile, Celexa, Nitalapram, "SSRI bicydic antidepressant", Celapram

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability:	1	
Toxicity:	2	
Body Contact:	2	
Reactivity:	1	
Chronic:	2	

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Possible risk of harm to the unborn child.

Very toxic to aquatic organisms.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be damaging to the health of the individual.

■ Aromatic nitriles, unlike aliphatic nitriles, do not appear to liberate cyanide within the body.

■ Serotonin syndrome (serious changes to how the brain, muscles and digestive system works due to high levels of serotonin in the body) may occur in therapy.

Signs and symptoms of serotonin syndrome include · restlessness · fast heart beat · fast changes in blood pressure · diarrhoea and vomiting · nausea · hallucinations · increased body temperature · coma · loss of coordination · overactive reflexes General side effects of serotonin reuptake inhibitors (SSRIs) are mostly present during the first 1-4 weeks while the body adapts to the drug (with the exception of sexual side effects, which tend to occur later in treatment).

EYE

■ Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn).

Slight abrasive damage may also result.

SKIN

■ Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

■ There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

■ This material is a photosensitizer.

Certain individuals working with this substance may show allergic reaction of the skin under sunlight.

■ Open cuts, abraded or irritated skin should not be exposed to this material.

■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified using animal models).

Nevertheless, adverse effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

■ Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

■ Results in experiments suggest that this material may cause disorders in the development of the embryo or fetus, even when no signs of poisoning show in the mother.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
citalopram	59729-33-8	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

· If swallowed do NOT induce vomiting. · If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

EYE

■ If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

INHALED

· If dust is inhaled, remove from contaminated area. · Encourage patient to blow nose to ensure clear passage of breathing. · If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

■ For selective serotonin reuptake inhibitors (SSRIs):

Serotonin toxicity is more pronounced following supra-therapeutic doses and overdoses, and they merge in a continuum with the toxic effects of overdose. The serotonergic toxicity of SSRIs increases with dose, but even in over-dose it is insufficient to cause fatalities from

serotonin syndrome in healthy adults. The syndrome occurs in approximately 14 to 16 percent of persons who overdose on SSRIs.

It is usually only when drugs with different mechanisms of action are mixed together that elevations of central nervous system serotonin reach potentially fatal levels.

The symptoms are often described as a clinical triad of abnormalities:

- Cognitive effects: mental confusion, hypomania, hallucinations, agitation, headache, coma.
- Autonomic effects: shivering, sweating, fever, hypertension, tachycardia, nausea, diarrhea.
- Somatic effects: myoclonus/clonus (muscle twitching), hyperreflexia, tremor.

Symptom onset is usually rapid, often occurring within minutes after self-poisoning or a change in medication. Serotonin syndrome encompasses a wide range of clinical findings. Mild symptoms may only consist of tachycardia, shivering, diaphoresis (sweating), mydriasis (dilated pupils), myoclonus (intermittent tremor or twitching), as well as overactive or over-responsive reflexes. Moderate intoxication includes additional abnormalities such as hyperactive bowel sounds, hypertension and hyperthermia; a temperature as high as 40 C (104 F) is common in moderate intoxication. The overactive reflexes and clonus in moderate cases may be greater in the lower limbs than in the upper limbs. Mental status changes include hyper-vigilance and agitation. Severe symptoms include severe hypertension and tachycardia that may lead to shock. Severe cases often have agitated delirium as well as muscular rigidity and high muscular tension. Temperature may rise to above 41.1 C (106.0 F) in life-threatening cases. Other abnormalities include metabolic acidosis, rhabdomyolysis, seizures, renal failure, and disseminated intravascular coagulation, these effects usually arise as a consequence of hyperthermia.

SSRIs appear to be safer in overdose when compared with traditional antidepressants such as the tricyclic antidepressants. This relative safety is supported both by case series and studies of deaths per numbers of prescriptions. However, case reports of SSRI poisoning have indicated that severe toxicity can occur and deaths have been reported following massive single ingestions, although this is exceedingly uncommon when compared to the tricyclic antidepressants.

Because of the wide therapeutic index of the SSRIs, most patients will have mild or no symptoms following moderate overdoses. The most commonly reported severe effect following SSRI overdose is serotonin syndrome; serotonin toxicity is usually associated with very high overdoses or multiple drug ingestion. Other reported significant effects include coma, seizures, and cardiac toxicity.

Treatment for SSRI overdose is mainly based on symptomatic and supportive care. Medical care may be required for agitation, maintenance of the airways, and treatment for serotonin syndrome. ECG monitoring is usually indicated to detect any cardiac abnormalities.

Supportive care includes:

- the control of agitation,
- the administration of serotonin antagonists (cyproheptadine or methysergide),
- the control of autonomic instability, and the control of hyperthermia.

The intensity of therapy depends on the severity of symptoms.

If the symptoms are mild, treatment may only consist of:

- discontinuation of the offending medication or medications,
- offering supportive measures,
- giving benzodiazepines for myoclonus, and waiting for the symptoms to resolve.

Moderate cases should have:

- all thermal and cardiorespiratory abnormalities corrected and
- can benefit from serotonin antagonists such as cyproheptadine.

Critically ill patients should receive the above therapies as well as:

- sedation, neuromuscular paralysis, and
- intubation with artificial ventilation.

Upon initiation of therapy and the discontinuation of serotonergic drugs most cases of serotonin syndrome resolve within 24 hours. Although delirium may persist for a number of days. Cases have reported muscle pain and weakness persisting for months although antidepressant withdrawal may contribute to ongoing features. Following appropriate medical management, serotonin syndrome is generally associated with a favorable prognosis.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Negligible
Upper Explosive Limit (%):	Not available
Specific Gravity (water=1):	Not available
Lower Explosive Limit (%):	Not available

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.

FIRE FIGHTING

- Alert Emergency Responders and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- Combustible solid which burns but propagates flame with difficulty.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), hydrogen fluoride, nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:
Chemical goggles.
Gloves:
Respirator:
Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Environmental hazard - contain spillage.
- Clean up waste regularly and abnormal spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.
- Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).
- Dampen with water to prevent dusting before sweeping.
- Place in suitable containers for disposal.

MAJOR SPILLS

- Environmental hazard - contain spillage.
- Moderate hazard.
- CAUTION: Advise personnel in area.
- Alert Emergency Responders and tell them location and nature of hazard.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
- Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.
- Do NOT cut, drill, grind or weld such containers.
 - In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

RECOMMENDED STORAGE METHODS

- Glass container.
- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- Observe manufacturer's storing and handling recommendations.


Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- citalopram: CAS:59729-33-8

PERSONAL PROTECTION



RESPIRATOR

Particulate
Consult your EHS staff for recommendations

EYE

- When handling very small quantities of the material eye protection may not be required.
- For laboratory, larger scale or bulk handling or where regular exposure in an occupational setting occurs:
- Chemical goggles
 - Face shield. Full face shield may be required for supplementary but never for primary protection of eyes
 - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their

removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

■ Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.

· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.

· Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

· Rubber gloves (nitrile or low-protein, powder-free latex). Employees allergic to latex gloves should use nitrile gloves in preference.

· Double gloving should be considered.

· PVC gloves.

· Protective shoe covers.

· Head covering.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

· polychloroprene

· nitrile rubber

· butyl rubber

· fluorocautchouc

· polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

OTHER

· For quantities up to 500 grams a laboratory coat may be suitable.

· For quantities up to 1 kilogram a disposable laboratory coat or coverall of low permeability is recommended. Coveralls should be buttoned at collar and cuffs.

· For quantities over 1 kilogram and manufacturing operations, wear disposable coverall of low permeability and disposable shoe covers.

· For manufacturing operations, air-supplied full body suits may be required for the provision of advanced respiratory protection.

· Eye wash unit.

· Ensure there is ready access to an emergency shower.

· For Emergencies: Vinyl suit.

ENGINEERING CONTROLS

■ Enclosed local exhaust ventilation is required at points of dust, fume or vapor generation.

HEPA terminated local exhaust ventilation should be considered at point of generation of dust, fumes or vapors.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

State	Divided solid	Molecular Weight	324.40
Melting Range (°F)	Not available	Viscosity	Not Applicable
Boiling Range (°F)	347- 358(0.03 mm)	Solubility in water (g/L)	Partly miscible
Flash Point (°F)	Not available	pH (1% solution)	Not applicable
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not available	Specific Gravity (water=1)	Not available
Lower Explosive Limit (%)	Not available	Relative Vapor Density (air=1)	Not Applicable
Volatile Component (%vol)	Negligible	Evaporation Rate	Not Applicable

APPEARANCE

White powder; does not mix with water.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

· Presence of incompatible materials.

· Product is considered stable.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

citalopram

TOXICITY AND IRRITATION

CITALOPRAM:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY IRRITATION

Oral (Human) LD: 56 mg/kg

Intraperitoneal (Mouse) LD50: 179 mg/kg

- No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Very toxic to aquatic organisms.

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

Refer to special instructions/ safety data sheets.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols: G Hazard class or Division: 9

Identification Numbers: UN3077 PG: III

Label Codes: 9 Special provisions: 8, 146,

335, B54,

IB8, IP3,

N20, T1,

TP33

Packaging: Exceptions: 155 Packaging: Non- bulk: 213

Packaging: Exceptions: 155 Quantity limitations: No limit

Passenger aircraft/rail:

Quantity Limitations: Cargo No limit Vessel stowage: Location: A aircraft only:

Vessel stowage: Other: None

Hazardous materials descriptions and proper shipping names:

Environmentally hazardous substance, solid, n.o.s

Air Transport IATA:

ICAO/IATA Class: 9 ICAO/IATA Subrisk: None
UN/ID Number: 3077 Packing Group: III
Special provisions: A97
Cargo Only
Packing Instructions: 400 kg Maximum Qty/Pack: 400 kg
Passenger and Cargo Passenger and Cargo
Packing Instructions: 956 Maximum Qty/Pack: 956
Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity
Packing Instructions: 30 kg G Maximum Qty/Pack: Y956
Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S. *(CONTAINS CITALOPRAM)

Maritime Transport IMDG:

IMDG Class: 9 IMDG Subrisk: None
UN Number: 3077 Packing Group: III
EMS Number: F-A , S-F Special provisions: 179 274 335 909
Limited Quantities: 5 kg Marine Pollutant: Yes
Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(contains citalopram)

Section 15 - REGULATORY INFORMATION

No data for citalopram (CAS: , 59729-33-8)

Section 16 - OTHER INFORMATION

ND

Substance CAS Suggested codes citalopram 59729- 33- 8 Xn; R22

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: May-26-2009

Print Date:Mar-22-2011