# Naringin hydrate

# sc-203443

**Material Safety Data Sheet** 



The Power to Questio

Hazard Alert Code Key:

**EXTREME** 

**HIGH** 

**MODERATE** 

LOW

# Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### **PRODUCT NAME**

Naringin hydrate

### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

#### NFΡΔ



#### **SUPPLIER**

Company: Santa Cruz Biotechnology, Inc.

Address:

2145 Delaware Ave Santa Cruz, CA 95060

Telephone: 800.457.3801 or 831.457.3800

Emergency Tel: CHEMWATCH: From within the US and

Canada: 877-715-9305

Emergency Tel: From outside the US and Canada: +800 2436

2255 (1-800-CHEMCALL) or call +613 9573 3112

### **PRODUCT USE**

Flavonoid isolated from the flowers of grapefruit trees (Citrus paradisi Macfad, Rutaceae), also in fruit and rind.

### SYNONYMS

C27-H32-O14, 7-[[2-O-(6-dehydroxy-alpha-L-mannopyranosyl)-beta-D-, glucopyranosyl]oxy]-, 7-[[2-O-(6-dehydroxy-alpha-L-mannopyranosyl)-beta-D-, glucopyranosyl]oxy]-, "2, 3-dihydro-5-hydroxy-2-(4-hydroxyphenyl)-4H-1-benzopyran-4-one", "2, 3-dihydro-5-hydroxy-2-(4-hydroxyphenyl)-4H-1-benzopyran-4-one", "4', 5, 7-trihydroxyflavanone 7-rhamnoglucoside", "4', 5, 7-trihydroxyflavanone 7-rhamnoglucoside", aurantiin, naringenin-7-beta-neohesperidoside, naringenin-7-beta-neohesperidoside, "natural product", "flavonoid/ phytooestrogen/ phytoestrogen"

# **Section 2 - HAZARDS IDENTIFICATION**

# **CANADIAN WHMIS SYMBOLS**



EMERGENCY OVERVIEW RISK POTENTIAL HEALTH EFFECTS ACUTE HEALTH EFFECTS

# **SWALLOWED**

■ The material has NOT been classified as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-

existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, unintentional ingestion is not thought to be cause for concern.

### EYE

■ Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.

#### SKIN

- The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

#### **INHALED**

- The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

#### CHRONIC HEALTH EFFECTS

■ There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray. Flavonoids, which are found in a range of foods and medicines, has been shown to cause leukemia in infancy, but, if taken at high levels in the diet, they reduce the risk of breast and prostate cancer.

Human and animal exposures to the phytooestrogens (for example the isoflavones, some flavonoids, saponin, coumestans and lignans) can be high because these compounds are found in many foods. Interest in the dietary phytooestrogens derives from their apparent protective effects against cancer, cardiovascular disease and osteoporosis. High levels, over extended periods, may produce toxic effects.

However, toxicological studies revealed that when administered in isolated or enriched form or at high doses isoflavones impair the function of the thyroid gland. It cannot be ruled out that this oestrogen-like effect also encourages the onset of breast cancer. Since women are more at risk of developing cancer in any case after menopause, the intake of food supplements with a high isoflavone content may present unexpected risks for this group of consumers.

Although phytooestrogens exist as the inactive glycoside in food products, bacterial beta-glycosidases, in the colon, hydrolyse the glycosides to the active aglycones.

A common feature of the phytooestrogens is their striking similarity to 17beta-oestrodiol and the synthetic oestrogen, diethylstilboestrol. There is evidence that phytooestrogens may mediate oestrogen-like effects by direct interaction with the oestrogen receptor of cells. Although the hormonal activity of phytooestrogens is two to five orders of magnitude below that of oestradiol, their high concentration in certain plants and their slower metabolic disposition, can lead to tissue levels exceeding those of endogenous oestrogens by a factor of a thousand or more.

There is also evidence that phytooestrogens may influence animal and human health by acting as antioxidants and hydrogen peroxide scavengers or by interfering with eicosanoid and cytokine production and cell signalling.

Anogenital distance, puberty onset, oestrus cycling, growth, sex-organ weight and hormonal profile are indicators of oestrogenor anti-oestrogen like activity. Of interest is the finding that low doses of the dietary isoflavone, genistein, taken by pregnant rats produced shorter anogenital distances in the offspring; high doses did not produce this effect. Exposure to a 5% flaxseed diet (high in lignans) during pregnancy and lactation, resulted in the delayed puberty onset in rats (anti-oestrogenic effect). By contrast, a 10% flaxseed diet produced an earlier onset of puberty (an oestrogenic effect), but longer oestrus cycles due to prolonged dioestrus (an antioestrogenic effect).

There have been many reports of phytooestrogens disrupting reproductive activity in sheep. Infertility in sheep (so-called "clover disease") has been traced to isoflavone concentrations in clover (up to 5% dry weight). Temporary infertility is attributed to increased embryo mortality and a reduction or cessation in ovulation. Permanent infertility, in sheep, is purported to occur after 3 years of exposure to dietary oestrogenic compounds; this infertility is due to permanent changes in the architecture of the cervix and also changes in the viscoelasticity of the cervical mucous which prevents the transport of sperm through the cervix. In addition to these effects, phytooestrogens exert effects on oestrogen-sensitive tissues such as the mammary gland and female reproductive organs of the ewe. Cattle have also been shown to be sensitive to the oestrogen-like effects of dietary phytooestrogens. Specific observations include swelling of the vulva, discharge of cervical mucous, uterus enlargements and cystic ovaries. Irregular oestrus cycles, including periods of anoestrus, and decreased rates of conception have also been reported. The impact on reproductive activity, by phytooestrogens on humans, is unknown.

The recent practice of feeding infants soy-based formula raises issues related to the long-term health effects of exposure during development. It has been recognised, for example, that the practice may be associated with goiter (thyroid enlargement associated with thyroid hormone deficiency) in humans and animals. Soy phytooestrogens inhibit thyroid hormone synthesis at concentrations which occur in infant formula.

If sufficient inhibition of iodide uptake by the goiter occurs, formation of thyroid hormones is depressed. These hormones are essential to the regulation of oxygen consumption and metabolism throughout the body. Clinical manifestations of this so-called "hypothyroidism (or athyrea)" include low metabolic rate, a tendency to gain weight, somnolence, and myxoedema (a relatively hard oedema of the subcutaneous tissue), dryness and loss of hair, low body temperature, hoarseness, muscle weakness, a slow return of the muscle after tendon jerk, and slow mentation. When hypothyroidism occurs in women, early in pregnancy, the foetus is at risk of impaired physical and mental development, the severity of the impairment depending on the degree of hypothyroidism.

# Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

### **HAZARD RATINGS**

Min Max

Flammability:

 NAME
 CAS RN
 %

 naringin
 10236-47-2
 >98

### **Section 4 - FIRST AID MEASURES**

### **SWALLOWED**

•

- · Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Center or a doctor.

### **EYE**

- If this product comes in contact with eyes:
- · Wash out immediately with water.
- · If irritation continues, seek medical attention.
- · Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

#### SKIN

- If skin or hair contact occurs:
- Flush skin and hair with running water (and soap if available).
- · Seek medical attention in event of irritation.

### **INHALED**

.

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

### **NOTES TO PHYSICIAN**

■ Treat symptomatically.

Section 5 -	<b>FIRE FIGHTING</b>	<b>MEASURES</b>
-------------	----------------------	-----------------

Vapour Pressure (mmHG):	Negligible
Hanor Evaloring Limit (0/)	Not available
Upper Explosive Limit (%):	Not available
Specific Gravity (water=1):	Not available
oposino Gravity (Mator 1).	Tot available
Lower Explosive Limit (%):	Not available
LOWER EXPROSIVE LITTIL (70).	Not available

# **EXTINGUISHING MEDIA**

•

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

### **FIRE FIGHTING**

•

- · Alert Emergency Responders and tell them location and nature of hazard.
- · Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

# GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- Combustible solid which burns but propagates flame with difficulty.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive
  mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the
  fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.
- Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
- Build-up of electrostatic charge may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO2), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

### FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids,chlorine bleaches, pool chlorine etc. as ignition may

result.

### PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves: Respirator: Particulate

# Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- Clean up all spills immediately.
- · Avoid breathing dust and contact with skin and eyes.
- · Wear protective clothing, gloves, safety glasses and dust respirator.
- · Use dry clean up procedures and avoid generating dust.
- Sweep up, shovel up or vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labeled container.

### MAJOR SPILLS

- Moderate hazard.
- CAUTION: Advise personnel in area.
- · Alert Emergency Responders and tell them location and nature of hazard.
- · Control personal contact by wearing protective clothing.
- · Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
- · If contamination of drains or waterways occurs, advise emergency services.

## ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

# **Section 7 - HANDLING AND STORAGE**

# PROCEDURE FOR HANDLING

•

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- · When handling, DO NOT eat, drink or smoke.
- · Keep containers securely sealed when not in use.
- · Avoid physical damage to containers.
- · Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.

- Do NOT cut, drill, grind or weld such containers
- In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

### RECOMMENDED STORAGE METHODS

- Polyethylene or polypropylene container.
- · Check all containers are clearly labelled and free from leaks.

### STORAGE REQUIREMENTS

- Store in original containers.
- · Keep containers securely sealed.
- · Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

# SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



- X: Must not be stored together
- O: May be stored together with specific preventions
- +: May be stored together

# Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### **EXPOSURE CONTROLS**

Source	Material	TWA ppm	TWA mg/m³		Peak mg/m³	TWA F/CC	Notes
US - Oregon Permissible Exposure Limits (Z3)	naringin (Inert or Nuisance Dust: (d) Total dust)		10				*
US OSHA Permissible Exposure Levels (PELs) - Table Z3	naringin (Inert or Nuisance Dust: (d) Respirable fraction)		5				
US OSHA Permissible Exposure Levels (PELs) - Table Z3	naringin (Inert or Nuisance Dust: (d) Total dust)		15				
US - Hawaii Air Contaminant Limits	naringin (Particulates not other wise regulated - Total dust)		10				
US - Hawaii Air Contaminant Limits	naringin (Particulates not other wise regulated - Respirable fraction)		5				
US - Oregon Permissible Exposure Limits (Z3)	naringin (Inert or Nuisance Dust: (d) Respirable fraction)		5				*
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	naringin (Particulates not otherwise regulated Respirable fraction)		5				
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	naringin (Particulates not otherwise regulated (PNOR)(f)- Respirable fraction)		5				
US - Michigan Exposure Limits for Air Contaminants	naringin (Particulates not otherwise regulated, Respirable dust)		5				

# **MATERIAL DATA**

NARINGIN:

■ It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

# PERSONAL PROTECTION



Consult your EHS staff for recommendations

### **EYE**

- •
- · Safety glasses with side shields
- · Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

#### HANDS/FEET

- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
- frequency and duration of contact,
- · chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene
- nitrile rubber
- · butyl rubber
- fluorocaoutchouc
- polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

### **OTHER**

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eve wash unit.

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

# **RESPIRATOR**

Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
10 x PEL	P1	-	PAPR-P1
	Air-line*	-	-
50 x PEL	Air-line**	P2	PAPR-P2
100 x PEL	-	P3	-
		Air-line*	-
100+ x PEL	-	Air-line**	PAPR-P3

<sup>\* -</sup> Negative pressure demand \*\* - Continuous flow

Explanation of Respirator Codes:

Class 1 low to medium absorption capacity filters.

Class 2 medium absorption capacity filters.

Class 3 high absorption capacity filters.

PAPR Powered Air Purifying Respirator (positive pressure) cartridge.

Type A for use against certain organic gases and vapors.

Type AX for use against low boiling point organic compounds (less than 65°C).

Type B for use against certain inorganic gases and other acid gases and vapors. Type E for use against sulfur dioxide and other acid gases and vapors.

Type K for use against ammonia and organic ammonia derivatives

Class P1 intended for use against mechanically generated particulates of sizes most commonly encountered in industry, e.g. asbestos, silica.

Class P2 intended for use against both mechanically and thermally generated particulates, e.g. metal fume.

Class P3 intended for use against all particulates containing highly toxic materials, e.g. beryllium.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

### **ENGINEERING CONTROLS**

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
- (a): particle dust respirators, if necessary, combined with an absorption cartridge;

- (b): filter respirators with absorption cartridge or canister of the right type;
- (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

Type of Contaminant:	Air Speed:
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)
Within each range the appropriate value depends on:	
Lower end of the range	Upper end of the range
1: Room air currents minimal or favorable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4. Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

# Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### **PHYSICAL PROPERTIES**

Solid

Does not mix with water.

State	Divided solid	Molecular Weight	580.59
Melting Range (°F)	339.8 (anhydride)	Viscosity	Not Applicable
Boiling Range (°F)	Not applicable	Solubility in water (g/L)	Immiscible
Flash Point (°F)	Not available	pH (1% solution)	Not applicable
Decomposition Temp (°F)	Not available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not available	Specific Gravity (water=1)	Not available
Lower Explosive Limit (%)	Not available	Relative Vapor Density (air=1)	Not applicable
Volatile Component (%vol)	Negligible	Evaporation Rate	Not applicable

### **APPEARANCE**

Off-white crystalline powder with bitter taste; does not mix with water (1gm dissolves in 1000 ml water; at 75 deg C 1gm dissolves in 10 ml water). Crystallises with 6-8 mole of water mp: 83 deg C. Dries at 110 deg C. 1:10,000 parts in water can be tasted. Soluble in acetone, alcohol, warm acetic acid.

# **Section 10 - CHEMICAL STABILITY**

# **CONDITIONS CONTRIBUTING TO INSTABILITY**

- Presence of incompatible materials.
- Product is considered stable.
- · Hazardous polymerization will not occur.

# STORAGE INCOMPATIBILITY

Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

# Section 11 - TOXICOLOGICAL INFORMATION

naringin

### **TOXICITY AND IRRITATION**

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY IRRITATION

### Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

NARINGIN:

■ DO NOT discharge into sewer or waterways.

# **Section 13 - DISPOSAL CONSIDERATIONS**

### **Disposal Instructions**

All waste must be handled in accordance with local, state and federal regulations.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licensed land-fill or Incineration in a licensed apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

### Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

# Section 15 - REGULATORY INFORMATION

naringin (CAS: 10236-47-2) is found on the following regulatory lists;

"Canada Domestic Substances List (DSL)","US Toxic Substances Control Act (TSCA) - Inventory"

### Section 16 - OTHER INFORMATION

# **LIMITED EVIDENCE**

- Cumulative effects may result following exposure\*.
- Limited evidence of a carcinogenic effect\*
- May possibly affect fertility\*.
- May possibly be harmful to the fetus/ embryo\*.
   \* (limited evidence).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references.
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Jun-13-2009 Print Date:Apr-21-2010