

# Etodolac

sc-204747

Material Safety Data Sheet



The Power is Question

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION


### PRODUCT NAME

Etodolac

### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### NFPA



### SUPPLIER

Santa Cruz Biotechnology, Inc.  
2145 Delaware Avenue  
Santa Cruz, California 95060  
800.457.3801 or 831.457.3800

### EMERGENCY:

ChemWatch  
Within the US & Canada: 877-715-9305  
Outside the US & Canada: +800 2436 2255  
(1-800-CHEMCALL) or call +613 9573 3112

### SYNONYMS

C17-H21-N-O3, "pyrano[3, 4-b]indole-1-acetic acid, 1, 8-diethyl-1, 3, 4, 9-tetrahydro-", "1, 8-diethyl-1, 3, 4, 9-tetrahydropyrano[3, 4-b]indole-1-acetic acid", "etodolic acid", AY-24236, Lodine, Ultradol, NSAID

## Section 2 - HAZARDS IDENTIFICATION

### CHEMWATCH HAZARD RATINGS

|               |   | Min | Max |
|---------------|---|-----|-----|
| Flammability: | 1 |     |     |
| Toxicity:     | 3 |     |     |
| Body Contact: | 3 |     |     |
| Reactivity:   | 1 |     |     |
| Chronic:      | 2 |     |     |

Min/Nil=0  
Low=1  
Moderate=2  
High=3  
Extreme=4



### CANADIAN WHMIS SYMBOLS



## EMERGENCY OVERVIEW

### RISK

Limited evidence of a carcinogenic effect.  
Toxic by inhalation, in contact with skin and if swallowed.

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

- Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual.
- Non-steroidal anti-inflammatory drug (NSAID) overdose may produce nausea, vomiting, indigestion and upper abdominal pain. Other effects may include drowsiness, dizziness, confusion, disorientation, lethargy, "pins and needles", intense headache, blurred vision, ringing in the ears, muscle twitching, convulsions, stupor and coma.

<p>

##### EYE

- Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.

<p>

##### SKIN

- Skin contact with the material may produce toxic effects; systemic effects may result following absorption.
- The material is not thought to be a skin irritant (as classified using animal models). Abrasive damage however, may result from prolonged exposures.

<p>

- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

##### INHALED

- Inhalation of dusts, generated by the material, during the course of normal handling, may produce toxic effects.
- The material is not thought to produce respiratory irritation (as classified using animal models). Nevertheless inhalation of dusts, or fume, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

#### CHRONIC HEALTH EFFECTS

- There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

<p>

Prolonged use of non-steroidal analgesics damages the lining of the gastrointestinal tract, causing ulcers and bleeding. There may be diarrhea or constipation, perforations causing serious infection, and blood in the vomit or stools.

<p>

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| NAME     | CAS RN     | %   |
|----------|------------|-----|
| Etodolac | 41340-25-4 | >98 |

## Section 4 - FIRST AID MEASURES

##### SWALLOWED

· Give a slurry of activated charcoal in water to drink. NEVER GIVE AN UNCONSCIOUS PATIENT WATER TO DRINK. · At least 3 tablespoons in a glass of water should be given.

##### EYE

- If this product comes in contact with the eyes: · Immediately hold eyelids apart and flush the eye continuously with running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

##### SKIN

- If skin or hair contact occurs: · Quickly but gently, wipe material off skin with a dry, clean cloth. · Immediately remove all contaminated

clothing, including footwear.

#### **INHALED**

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

#### **NOTES TO PHYSICIAN**

■ Treat symptomatically.

for poisons (where specific treatment regime is absent):

-----BASIC TREATMENT

· Establish a patent airway with suction where necessary.

· Watch for signs of respiratory insufficiency and assist ventilation as necessary.

Absorbed from the gastrointestinal tract and is highly bound to plasma proteins with a reported half-life of about 7 hours. Excreted predominantly in the urine as hydroxylated metabolites and glucuronide conjugates.

### **Section 5 - FIRE FIGHTING MEASURES**

|                             |                |
|-----------------------------|----------------|
| Vapour Pressure (mmHG):     | Negligible     |
| Upper Explosive Limit (%):  | Not available. |
| Specific Gravity (water=1): | Not available. |
| Lower Explosive Limit (%):  | Not available. |

#### **EXTINGUISHING MEDIA**

· Foam.

· Dry chemical powder.

#### **FIRE FIGHTING**

· Alert Emergency Responders and tell them location and nature of hazard.

· Wear full body protective clothing with breathing apparatus.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

#### **GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS**

· Combustible solid which burns but propagates flame with difficulty.

· Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

#### **FIRE INCOMPATIBILITY**

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

#### **PERSONAL PROTECTION**

Glasses:

Gloves:

Respirator:

Particulate

### **Section 6 - ACCIDENTAL RELEASE MEASURES**

#### **MINOR SPILLS**

· Clean up waste regularly and abnormal spills immediately.

· Avoid breathing dust and contact with skin and eyes.

· Wear protective clothing, gloves, safety glasses and dust respirator.

· Use dry clean up procedures and avoid generating dust.

· Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).

· Dampen with water to prevent dusting before sweeping.

· Place in suitable containers for disposal.

#### **MAJOR SPILLS**

· Clear area of personnel and move upwind.

· Alert Emergency Responders and tell them location and nature of hazard.

### **Section 7 - HANDLING AND STORAGE**

#### **PROCEDURE FOR HANDLING**

· Avoid all personal contact, including inhalation.

· Wear protective clothing when risk of exposure occurs.

Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.

- Do NOT cut, drill, grind or weld such containers.
- In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

### RECOMMENDED STORAGE METHODS

- Packaging as recommended by manufacturer.
- Check that containers are clearly labelled.
- Tamper-proof containers.
- Polyethylene or polypropylene containers.
- Metal drum with sealed plastic liner.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

| Source                                                                           | Material                                                                      | TWA ppm | TWA mg/m³ | STEL ppm | STEL mg/m³ | Peak ppm | Peak mg/m³ | TWA F/CC | Notes                               |
|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------|---------|-----------|----------|------------|----------|------------|----------|-------------------------------------|
| US - California Permissible Exposure Limits for Chemical Contaminants            | Etodolac (Particulates not otherwise regulated Respirable fraction)           |         | 5         |          |            |          |            |          | (n)                                 |
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants        | Etodolac (Particulates not otherwise regulated Respirable fraction)           |         | 5         |          |            |          |            |          |                                     |
| US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants | Etodolac (Particulates not otherwise regulated (PNOR)(f)-Respirable fraction) |         | 5         |          |            |          |            |          |                                     |
| US - Michigan Exposure Limits for Air Contaminants                               | Etodolac (Particulates not otherwise regulated, Respirable dust)              |         | 5         |          |            |          |            |          |                                     |
| Canada - Prince Edward Island Occupational Exposure Limits                       | Etodolac (Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles)  |         | 10        |          |            |          |            |          | See Appendix B current TLV/BEI Book |

ENDOELTABLE

### PERSONAL PROTECTION



### RESPIRATOR

Particulate

Consult your EHS staff for recommendations

## EYE

■ For laboratory, larger scale or bulk handling or where regular exposure in an occupational setting occurs:

- Chemical goggles
- Face shield. Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

## HANDS/FEET

■ Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- Rubber gloves (nitrile or low-protein, powder-free latex). Employees allergic to latex gloves should use nitrile gloves in preference.
- Double gloving should be considered.
- PVC gloves.
- Protective shoe covers.
- Head covering.

## OTHER

- For quantities up to 500 grams a laboratory coat may be suitable.
- For quantities up to 1 kilogram a disposable laboratory coat or coverall of low permeability is recommended. Coveralls should be buttoned at collar and cuffs.
- For quantities over 1 kilogram and manufacturing operations, wear disposable coverall of low permeability and disposable shoe covers.
- For manufacturing operations, air-supplied full body suits may be required for the provision of advanced respiratory protection.
- Eye wash unit.
- Ensure there is ready access to an emergency shower.
- For Emergencies: Vinyl suit.

## ENGINEERING CONTROLS

■ For potent pharmacological agents:

### Powders

To prevent contamination and overexposure, no open handling of powder should be allowed.

- Powder handling operations are to be done in a powders weighing hood, a glove box, or other equivalent ventilated containment system.
- In situations where these ventilated containment hoods have not been installed, a non-ventilated enclosed containment hood should be used.
- Pending changes resulting from additional air monitoring data, up to 300 mg can be handled outside of an enclosure provided that no grinding, crushing or other dust-generating process occurs.
- An air-purifying respirator should be worn by all personnel in the immediate area in cases where non-ventilated containment is used, where significant amounts of material (e.g., more than 2 grams) are used, or where the material may become airborne (as through grinding, etc.).
- Powder should be put into solution or a closed or covered container after handling.
- If using a ventilated enclosure that has not been validated, wear a half-mask respirator equipped with HEPA cartridges until the enclosure is validated for use.

### Solutions Handling:

- Solutions can be handled outside a containment system or without local exhaust ventilation during procedures with no potential for aerosolisation. If the procedures have a potential for aerosolisation, an air-purifying respirator is to be worn by all personnel in the immediate area.
- Solutions used for procedures where aerosolisation may occur (e.g., vortexing, pumping) are to be handled within a containment system or with local exhaust ventilation.
- In situations where this is not feasible (may include animal dosing), an air-purifying respirator is to be worn by all personnel in the immediate area. If using a ventilated enclosure that has not been validated, wear a half-mask respirator equipped with HEPA cartridges until the enclosure is validated for use.
- Ensure gloves are protective against solvents in use.

Unless written procedures, specific to the workplace are available, the following is intended as a guide:

- For Laboratory-scale handling of Substances assessed to be toxic by inhalation. Quantities of up to 25 grams may be handled in Class II biological safety cabinets\*; Quantities of 25 grams to 1 kilogram may be handled in Class II biological safety cabinets\* or equivalent containment systems Quantities exceeding 1 kg may be handled either using specific containment, a hood or Class II biological safety cabinet\*,
- HEPA terminated local exhaust ventilation should be considered at point of generation of dust, fumes or vapors.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

## PHYSICAL PROPERTIES

Solid.

Does not mix with water.

|                           |                |                                |                 |
|---------------------------|----------------|--------------------------------|-----------------|
| State                     | Divided solid  | Molecular Weight               | 287.37          |
| Melting Range (°F)        | 293- 298.4     | Viscosity                      | Not Applicable  |
| Boiling Range (°F)        | Not available. | Solubility in water (g/L)      | Partly miscible |
| Flash Point (°F)          | Not available  | pH (1% solution)               | Not applicable  |
| Decomposition Temp (°F)   | Not Available  | pH (as supplied)               | Not applicable  |
| Autoignition Temp (°F)    | Not available. | Vapour Pressure (mmHG)         | Negligible      |
| Upper Explosive Limit (%) | Not available. | Specific Gravity (water=1)     | Not available.  |
| Lower Explosive Limit (%) | Not available. | Relative Vapor Density (air=1) | Not applicable  |
| Volatile Component (%vol) | Negligible     | Evaporation Rate               | Not applicable  |

## APPEARANCE

White crystalline solid; does not mix well with water.

## Section 10 - CHEMICAL STABILITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

### STORAGE INCOMPATIBILITY

- Avoid oxidizing agents, acids, acid chlorides, acid anhydrides.
- Avoid exposure to light and air.

For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

ETODOLAC

### TOXICITY AND IRRITATION

#### ETODOLAC:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

| TOXICITY                                | IRRITATION   |
|-----------------------------------------|--------------|
| Oral (rat) LD50: 94 mg/kg               | Nil Reported |
| Subcutaneous (rat) LD50: 113 mg/kg      |              |
| Oral (mouse) LD50: 593 mg/kg            |              |
| Intraperitoneal (mouse) LD50: 338 mg/kg |              |
| Subcutaneous (mouse) LD50: 502 mg/kg    |              |

## Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

### Ecotoxicity

|            |                            |                  |                 |          |
|------------|----------------------------|------------------|-----------------|----------|
| Ingredient | Persistence:<br>Water/Soil | Persistence: Air | Bioaccumulation | Mobility |
| Etodolac   | HIGH                       |                  | LOW             | MED      |

## Section 13 - DISPOSAL CONSIDERATIONS

### Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

## Section 14 - TRANSPORTATION INFORMATION

DOT:

Symbols: None Hazard class or Division: 6.1

Identification Numbers: UN3249 PG: III

Label Codes: 6.1 Special provisions: T1, TP33

Packaging: Exceptions: 153 Packaging: Non- bulk: 213

Packaging: Exceptions: 153 Quantity limitations: 5 kg

Passenger aircraft/rail:

Quantity Limitations: Cargo 5 kg Vessel stowage: Location: C aircraft only:

Vessel stowage: Other: 40

Hazardous materials descriptions and proper shipping names:

Medicine, solid, toxic, n.o.s.

### Air Transport IATA:

ICAO/IATA Class: 6.1 ICAO/IATA Subrisk: None

UN/ID Number: 3249 Packing Group: III

Special provisions: A3

Cargo Only

Packing Instructions: 615 Maximum Qty/Pack: 5 kg

Passenger and Cargo Passenger and Cargo

Packing Instructions: 613 Maximum Qty/Pack: 5 kg

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: Y613 Maximum Qty/Pack: 5 kg

Shipping Name: MEDICINE, SOLID, TOXIC, N.O.S.(CONTAINS ETODOLAC)

### Maritime Transport IMDG:

IMDG Class: 6.1 IMDG Subrisk: None

UN Number: 3249 Packing Group: III

EMS Number: F-A , S-A Special provisions: 221 223

Limited Quantities: 5 kg

Shipping Name: MEDICINE, SOLID, TOXIC, N.O.S.

## Section 15 - REGULATORY INFORMATION

**Etodolac (CAS: 41340-25-4) is found on the following regulatory lists;**

"Canada Domestic Substances List (DSL)", "US - California Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity", "US - California Proposition 65 - Reproductive Toxicity", "US - Maine Chemicals of High Concern List"

## Section 16 - OTHER INFORMATION

### LIMITED EVIDENCE

- Cumulative effects may result following exposure\*.

\* (limited evidence).

*Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.*

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: Feb-24-2009

Print Date:Nov-18-2010