13-OxoODE: sc-204993



MATERIAL SAFETY DATA SHEET

The Power to Question

1. Product and Company Identification

Product Name: 13-OxoODE
Catalog Number: sc-204993

Supplier: Santa Cruz Biotechnology, Inc.

2145 Delaware Avenue Santa Cruz, California 95060 800.457.3801 or 831.457.3800

Chemical Family: Oxo Fatty Acids

Synonyms: 13-oxo-9Z,11E-octadecadienoic acid; 13-KODE

Emergency:

ChemWatch

Within the US & Canada: 877-715-9305 Outside the US & Canada: +800 2436 2255 (1-800-CHEMCALL) or call +613 9573 3112

Composition/Information on Ingredients							
Hazardous Components (Chemical Name)	CAS#	Percentage	OSHA PEL	ACGIH TLV	Other Limits		
1. 13-OxoODE	54739-30-9	0.01 %	No data.	No data.	No data.		
2. Ethyl alcohol	64-17-5	99.99 %	8H TWA:1000 ppm	1000 ppm	No data.		
			(1900 mg/m3)				
Hazardous Components (Chemical Name)	RTECS#	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL		
1. 13-OxoODE	NA	No data.	No data.	No data.	No data.		
2. Ethyl alcohol	KQ6300000	No data.	No data.	No data.	No data.		
2 Hazarda Idontification							

Hazards Identification

Emergency Overview: No data available.

Route(s) of Entry: Inhalation? Yes Skin? Yes Eyes? Yes Ingestion? Yes Other: Injection **Potential Health Effects (Acute and Chronic):** The hazards identified with this product are those associated with the solvent(s).

Long term repeated oral exposure to ethanol may result in the development of progressive liver

injury with fibrosis.

Material is irritating to the mucous membranes and upper respiratory tract.

May be harmful by inhalation, ingestion, or skin absorption. May cause eye, skin, or respiratory system irritation. Repeated exposure may cause skin dryness or cracking.

Repeated ingestion of ethanol by pregnant mothers has been shown to adversely affect the CNS system of the fetus, producing a collection of effects which together consitutue fetal alcohol syndrome. These include mental and physical retardation, disturbances of learning, motor and

language deficiencies, behavioral disorders and small size head.

The toxicological properties of this compound have not been fully evaluated. Exposure may cause: Dizziness, drowsiness, headache, nausea, and vomiting.

Medical Conditions Generally Aggravated By Repeated exposure to ethanol may aggravate liver injury produced from other causes.

Exposure:

4. First Aid Measures

Emergency and First Aid Procedures:

Signs and Symptoms Of Exposure:

If inhaled remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Get immediate medical attention.

If swallowed, wash out mouth with water provided person is conscious. Never give anything by mouth to an unconscious person. Get medical attention. Do NOT induce vomiting unless directed to do so by medical personnel.

In case of contact with eyes, hold eyelids apart and flush eyes with plenty of water. After initial flushings, remove any contact lenses and continue flushing for at least 20 minutes. Have eyes examined and tested by medical personnel.

In case of skin contact, immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

5. Fire Fighting Measures

Flash Pt: 14.00 C Method Used: TCC

Explosive Limits: LEL: 3.3% at 25.0 C UEL: 19% at 25.0 C

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSHa

pproved or equivalent), and full protective gear to prevent contact with skin and eyes.

Note: Flammable as diluted in ethanol.

Flammable Properties and Hazards: Can release vapors that form explosive mixtures at temperatures at or above the flashpoint.

Container explosion may occur under fire conditions.

Emits toxic fumes under fire conditions.

Flammable liquid.

Vapors can travel to a source of ignition and flash back.

Hazardous Combustion Products: carbon dioxide

carbon monoxide

Extinguishing Media: Use alcohol-resistant foam, carbon dioxide, water, or dry chemical spray when fighting fires

involving this material.

Unsuitable Extinguishing Media: No data available.

Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:

Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. After removal, ventilate contaminated area and flush thoroughly with water.

Handling and Storage

Do not reuse this container. Use with adequate ventilation. **Hazard Label Information:** Avoid contact with skin and eyes.

Wash thoroughly after handling.

Precautions To Be Taken in Handling: Avoid breathing (dust, vapor, mist, gas).

> Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated exposure.

Do not reuse this container.

Keep away from sources of ignition. Use with adequate ventilation. Wash thoroughly after handling.

Precautions To Be Taken in Storing: Store at correct temperature.

Exposure Controls/Personal Protection

Protective Equipment Summary - Hazard

Label Information:

Eye wash station in work area Lab coat Latex disposable gloves Safety glasses Safety

shower in work area Vent Hood

Respiratory Equipment (Specify Type): No data available. **Eye Protection:**

Safety glasses

Protective Gloves: Latex disposable gloves

Other Protective Clothing: Lab coat

Engineering Controls (Ventilation etc.): Good general ventilation should be sufficient to control airborne levels.

Work/Hygienic/Maintenance Practices: Do not take internally.

Facilities storing or utilizing this material should be equipped with an eyewash facility and a

safety shower.

Wash thoroughly after handling.

Physical and Chemical Properties

Physical States: [] Gas [X] Liquid

Melting Point: No data. **Boiling Point:** No data. **Autoignition Pt:** No data.

Flash Pt: 14.00 C Method: TCC

Explosive Limits: UEL: 19% at 25.0 C LEL: 3.3% at 25.0 C

Specific Gravity (Water = 1): No data.

Vapor Pressure (vs. Air or mm Hg): 44.6 MM HG at 20.0 C

Vapor Density (vs. Air = 1): No data. Evaporation Rate (vs Butyl Acetate=1): No data.

Solubility in Water: > 1 mg/ml* at 25.0 C

Other Solubility Notes: *PBS pH 7.2, also sol. in EtOH, DMSO, & DMF

Percent Volatile: N.A. **Corrosion Rate:** No data. Formula: C18H30O3 Molecular Weight: 294.40

pH: No data.

Appearance and Odor: A clear, colorless solution.

10. Stability and Reactivity

Stability: Stable [X] Unstable [

Conditions To Avoid - Instability: No data available. Incompatibility - Materials To Avoid: strong inorganic acids strong oxidizing agents

Hazardous Decomposition Or Byproducts: carbon dioxide

carbon monoxide

No data available.

Hazardous Polymerization: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous

Polymerization:

11. Toxicological Information

Toxicological Information: The toxicological effects of this compound have not been thoroughly studied.

Carcinogenicity/Other Information: No data available.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. Ecological Information

Runoff from fire control or dilution water may cause pollution. **Ecological Information:**

Disposal Considerations

Waste Disposal Method: Dispose in accordance with local, state and federal regulations.

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name: Ethyl alcohol

DOT Hazard Class:

DOT Hazard Label: FLAMMABLE LIQUID

UN/NA Number: 1170 **DOT Packing Group:** Π

Additional Transport Information: Transport in accordance with local, state, and federal regulations.

15. Regulatory Information

US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS#	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. 13-OxoODE	54739-30-9	No	No	No	No
2. Ethyl alcohol	64-17-5	No	No	No	No

US EPA CAA, CWA, TSCA

Hazardous Components (Chemical Name)	CAS#	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65		
1. 13-OxoODE	54739-30-9	No	No	No	No		
Hazardous Components (Chemical Name)	CAS#	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65		
2. Ethyl alcohol	64-17-5	No	No	No	No		
40.00							

Other Information

The above information is believed to be correct but does not purport to be complete and should be used only as a guide. The burden of safe use of this material rests entirely with the user.

11/29/2010