# **Mabuterol**

# sc-211757

**Material Safety Data Sheet** 



The Power to Oscotion

Hazard Alert Code Key: EXTREME HIGH MODERATE LOW

### Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

# **PRODUCT NAME**

Mabuterol

#### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### **NFPA**



### **SUPPLIER**

Santa Cruz Biotechnology, Inc. 2145 Delaware Avenue Santa Cruz, California 95060 800.457.3801 or 831.457.3800

# **EMERGENCY** ChemWatch

Within the US & Canada: 877–715–9305
Outside the US & Canada: +800 2436 2255


(1-800-CHEMCALL) or call +613 9573 3112

## **SYNONYMS**

C13-H18-Cl-F3-N2-O, 1-[4-amino-3-chloro-5-(trifluoromethyl)phenyl]-2-(tert-, butylamino)ethanol, "4-amino-3-chloro-a-[[(1, 1-dimethylethyl)amino]methyl]-5-", (trifluoromethyl)benzenemethanol, 4-amino-alpha-[(tert-butylamino)methyl]-3-chloro-5-, "(trifluoromethyl)benzyl alcohol 1-(4' -amino-3' -chloro-5' -", trifluoromethylphenyl)-2-tert-butylaminoethanol;, ambuterol, "beta-adrenergic agonist", bronchodilator, "ephedrine derivative"

### **Section 2 - HAZARDS IDENTIFICATION**

### CHEMWATCH HAZARD RATINGS



#### **CANADIAN WHMIS SYMBOLS**



## **EMERGENCY OVERVIEW**

#### **RISK**

May cause SENSITISATION by skin contact.

#### **POTENTIAL HEALTH EFFECTS**

#### **ACUTE HEALTH EFFECTS**

#### **SWALLOWED**

■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

#### **FYF**

■ Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn).

Slight abrasive damage may also result.

#### SKIN

■ Skin contact is not thought to produce harmful health effects (as classified using animal models).

Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions.

- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

#### **INHALED**

- Inhalation of dusts, generated by the material, during the course of normalhandling, may be harmful.
- The material is not thought to produce respiratory irritation (as classified using animal models).

Nevertheless inhalation of dusts, or fume, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.
- Sympathomimetics, which mimic stimulation of the sympathetic nerves, causing a stimulatory effect on the heart and central nervous system, constriction of blood vessels supplying the skin and mucous membranes, dilation of blood vessels supplying muscles of movement, and widening of the airways.

These drugs may act on the receptor or the release of the neurotransmitter noradrenaline.

■ Stimulation of heart beta-1 adrenergic receptors may cause increased heart rate and irregularity of heartbeat, tightness and a constricting pain in the chest, palpitations and heart stoppage; low blood pressure with dizziness, fainting and flushing may also occur.

Beta-1 receptors mediate the action of sympathomimetics; beta-2 receptors control dilation of the airways.

#### **CHRONIC HEALTH EFFECTS**

■ Skin contact with the material is more likely to cause a sensitization reaction in some persons compared to the general population. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

# Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

 NAME
 CAS RN
 %

 mabuterol
 56341-08-3
 >98

#### Section 4 - FIRST AID MEASURES

#### **SWALLOWED**

· IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. · Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

#### **EYE**

■ If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

#### SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

#### INHALED

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

#### **NOTES TO PHYSICIAN**

- for isoprenaline intoxication:
- · Tachycardia and cardiac arrhythmias induced by beta-2-adrenergic agonists may be diminished by propranolol but this must NOT be given

to asthmatics because of the risk of increasing bronchoconstriction.

· Cautious use of cardioselective beta-adrenergic blocking agents such as metaprolol (5-10 mg by slow intravenous injection, repeated if necessary after 5 minutes) may be indicated in asthma patients.

MARTINDALE & AAP Guide.

Section 5 - FIRE FIGHTING MEASURES				
Vapour Pressure (mmHG):	Negligible			
Upper Explosive Limit (%):	Not Available			
Specific Gravity (water=1):	Not Available			
Lower Explosive Limit (%):	Not Available			

#### **EXTINGUISHING MEDIA**

- · Foam.
- · Dry chemical powder.

#### **FIRE FIGHTING**

- · Alert Emergency Responders and tell them location and nature of hazard.
- · Wear full body protective clothing with breathing apparatus.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

#### GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- · Combustible solid which burns but propagates flame with difficulty.
- · Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO2), hydrogen chloride, phosgene, hydrogen fluoride, nitrogen oxides (NOx), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

#### FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

#### PERSONAL PROTECTION

Glasses:

Gloves:

Respirator: Particulate

## Section 6 - ACCIDENTAL RELEASE MEASURES

#### MINOR SPILLS

- · Clean up waste regularly and abnormal spills immediately.
- · Avoid breathing dust and contact with skin and eyes.
- · Wear protective clothing, gloves, safety glasses and dust respirator.
- · Use dry clean up procedures and avoid generating dust.
- · Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).
- · Dampen with water to prevent dusting before sweeping.
- · Place in suitable containers for disposal.

#### MAJOR SPILLS

- $\cdot$  Clear area of personnel and move upwind.
- $\cdot$  Alert Emergency Responders and tell them location and nature of hazard.

## **Section 7 - HANDLING AND STORAGE**

#### PROCEDURE FOR HANDLING

- · Avoid all personal contact, including inhalation.
- · Wear protective clothing when risk of exposure occurs.

Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.

- · Do NOT cut, drill, grind or weld such containers.
- · In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

## **RECOMMENDED STORAGE METHODS**

- Glass container.
- $\cdot$  Lined metal can, Lined metal pail/drum
- · Plastic pail.

For low viscosity materials

 $\cdot$  Drums and jerricans must be of the non-removable head type.

· Where a can is to be used as an inner package, the can must have a screwed enclosure.

#### STORAGE REQUIREMENTS

- · Store in original containers.
- · Keep containers securely sealed.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **EXPOSURE CONTROLS**

The following materials had no OELs on our records

• mabuterol: CAS:56341-08-3 CAS:56707-24-5

#### PERSONAL PROTECTION









#### **RESPIRATOR**

Particulate

Consult your EHS staff for recommendations

#### **EYE**

- For laboratory, larger scale or bulk handling or where regular exposure in an occupational setting occurs:
- · Chemical goggles
- · Face shield. Full face shield may be required for supplementary but never for primary protection of eyes
- · Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

#### HANDS/FEET

■ NOTE: The material may produce skin sensitization in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- · frequency and duration of contact,
- chemical resistance of glove material,
- · glove thickness and
- · dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- · Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- · Rubber gloves (nitrile or low-protein, powder-free latex). Employees allergic to latex gloves should use nitrile gloves in preference.
- · Double gloving should be considered.
- · PVC gloves.
- · Protective shoe covers.
- · Head covering.

#### OTHER

- $\cdot$  For quantities up to 500 grams a laboratory coat may be suitable.
- · For quantities up to 1 kilogram a disposable laboratory coat or coverall of low permeability is recommended. Coveralls should be buttoned at collar and cuffs.
- · For quantities over 1 kilogram and manufacturing operations, wear disposable coverall of low permeability and disposable shoe covers.
- For manufacturing operations, air-supplied full body suits may be required for the provision of advanced respiratory protection.
- · Eve wash unit.
- $\cdot$  Ensure there is ready access to an emergency shower.
- · For Emergencies: Vinyl suit.

## **ENGINEERING CONTROLS**

■ Enclosed local exhaust ventilation is required at points of dust, fume or vapor generation.

HEPA terminated local exhaust ventilation should be considered at point of generation of dust, fumes or vapors.

## **Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

#### **PHYSICAL PROPERTIES**

State	Divided Solid	Molecular Weight	310.74
Melting Range (°F)	Not Available	Viscosity	Not Applicable
Boiling Range (°F)	Not Applicable	Solubility in water (g/L)	Partly Miscible
Flash Point (°F)	Not Available	pH (1% solution)	Not Applicable
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°F)	Not Available	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	Not Available
Lower Explosive Limit (%)	Not Available	Relative Vapor Density (air=1)	Not Applicable
Volatile Component (%vol)	Negligible	Evaporation Rate	Not Applicable

#### **APPEARANCE**

Crystalline solid; does not mix well with water.

#### Section 10 - CHEMICAL STABILITY

#### **CONDITIONS CONTRIBUTING TO INSTABILITY**

- · Presence of incompatible materials.
- · Product is considered stable.

#### STORAGE INCOMPATIBILITY

· Protect from light.

Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

#### Section 11 - TOXICOLOGICAL INFORMATION

mabuterol

#### **TOXICITY AND IRRITATION**

### **MABUTEROL:**

- unless otherwise specified data extracted from RTECS Register of Toxic Effects of Chemical Substances.
- Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's edema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.

  No significant acute toxicological data identified in literature search.

### **Section 12 - ECOLOGICAL INFORMATION**

This material and its container must be disposed of as hazardous waste.

**Ecotoxicity** 

Ingredient Persistence: Water/Soil Persistence: Air Bioaccumulation Mobility mabuterol LOW HIGH

## **Section 13 - DISPOSAL CONSIDERATIONS**

#### **Disposal Instructions**

All waste must be handled in accordance with local, state and federal regulations.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- · Reuse
- Recycling
- · Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- · Recycle wherever possible.
- · Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

#### Section 14 - TRANSPORTATION INFORMATION

DOT:

Symbols: None Hazard class or Division: 6.1 Identification Numbers: UN3249 PG: III Label Codes: 6.1 Special provisions: T1, TP33 Packaging: Exceptions: 153 Packaging: Non- bulk: 213 Packaging: Exceptions: 153 Quantity limitations: 5 kg

Passenger aircraft/rail:

Quantity Limitations: Cargo 5 kg Vessel stowage: Location: C

aircraft only:

Vessel stowage: Other: 40

Hazardous materials descriptions and proper shipping names:

Medicine, solid, toxic, n.o.s. **Air Transport IATA:** 

ICAO/IATA Class: 6.1 ICAO/IATA Subrisk: None UN/ID Number: 3249 Packing Group: III

Special provisions: A3

Cargo Only

Packing Instructions: 5 kg Maximum Qty/Pack: 5 kg Passenger and Cargo Passenger and Cargo Packing Instructions: 615 Maximum Qty/Pack: 613

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: 5 kg Maximum Qty/Pack: Y613

Shipping Name: MEDICINE, SOLID, TOXIC, N.O.S.(CONTAINS

MABUTEROL)

**Maritime Transport IMDG:** 

IMDG Class: 6.1 IMDG Subrisk: None UN Number: 3249 Packing Group: III

EMS Number: F-A, S-A Special provisions: 221 223

Limited Quantities: 5 kg

Shipping Name: MEDICINE, SOLID, TOXIC, N.O.S.

## **Section 15 - REGULATORY INFORMATION**

No data for mabuterol (CAS: , 56341-08-3, 56707-24-5)

### Section 16 - OTHER INFORMATION

#### Ingredients with multiple CAS Nos

Ingredient Name CAS mabuterol 56341-08-3, 56707-24-5

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

  A list of reference resources used to assist the committee may be found at:

  www.chemwatch.net/references.
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Nov-10-2010 Print Date: Feb-22-2011