

# Cholesteryl acetate

sc-214693

Material Safety Data Sheet



The Power is Question

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION


### PRODUCT NAME

Cholesteryl acetate

### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### NFPA



### SUPPLIER

Santa Cruz Biotechnology, Inc.  
2145 Delaware Avenue  
Santa Cruz, California 95060  
800.457.3801 or 831.457.3800

### EMERGENCY

ChemWatch  
Within the US & Canada: 877-715-9305  
Outside the US & Canada: +800 2436 2255  
(1-800-CHEMCALL) or call +613 9573 3112

### SYNONYMS

C29-H48-O2, "cholesterol acetate", "cholest-5-en-3beta-yl acetate", 3beta-acetoxy-5-cholestene, 5-cholesten-3beta-ol-3-acetate, "3beta-hydroxy-5-cholestene 3-acetate"

## Section 2 - HAZARDS IDENTIFICATION

### CHEMWATCH HAZARD RATINGS

|               |   | Min | Max |
|---------------|---|-----|-----|
| Flammability: | 1 |     |     |
| Toxicity:     | 2 |     |     |
| Body Contact: | 2 |     |     |
| Reactivity:   | 1 |     |     |
| Chronic:      | 0 |     |     |

Min/Nil=0  
Low=1  
Moderate=2  
High=3  
Extreme=4

### CANADIAN WHMIS SYMBOLS

None

### EMERGENCY OVERVIEW

### RISK

### POTENTIAL HEALTH EFFECTS

### ACUTE HEALTH EFFECTS

## SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual.
- Nonionic surfactants may produce localized irritation of the oral or gastrointestinal lining and induce vomiting and mild diarrhea.

## EYE

- There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
- Non-ionic surfactants can cause numbing of the cornea, which masks discomfort normally caused by other agents and leads to corneal injury.

Irritation varies depending on the duration of contact, the nature and concentration of the surfactant.

## SKIN

- The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
- Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

## INHALED

- The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified using animal models). Nevertheless, adverse effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

## CHRONIC HEALTH EFFECTS

- Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified using animal models); nevertheless exposure by all routes should be minimized as a matter of course.
- Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.
- Prolonged or repeated skin contact may cause degreasing with drying, cracking and dermatitis following.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| NAME                | CAS RN   | %   |
|---------------------|----------|-----|
| cholesteryl acetate | 604-35-3 | >98 |

## Section 4 - FIRST AID MEASURES

### SWALLOWED

· If swallowed do NOT induce vomiting. · If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

### EYE

- If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

### SKIN

- If skin or hair contact occurs: · Flush skin and hair with running water (and soap if available). · Seek medical attention in event of irritation.

### INHALED

· If dust is inhaled, remove from contaminated area. · Encourage patient to blow nose to ensure clear passage of breathing. · If irritation or discomfort persists seek medical attention.

### NOTES TO PHYSICIAN

- Treat symptomatically.

## Section 5 - FIRE FIGHTING MEASURES

|                             |                |
|-----------------------------|----------------|
| Vapour Pressure (mmHG):     | Negligible     |
| Upper Explosive Limit (%):  | Not available. |
| Specific Gravity (water=1): | Not available  |
| Lower Explosive Limit (%):  | Not available  |

### EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.

### FIRE FIGHTING

- Alert Emergency Responders and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.

## GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- Combustible solid which burns but propagates flame with difficulty.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

## FIRE INCOMPATIBILITY

- Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Control personal contact by using protective equipment.
- Use dry clean up procedures and avoid generating dust.
- Place in a suitable, labelled container for waste disposal.

### MAJOR SPILLS

- Moderate hazard.
- CAUTION: Advise personnel in area.
- Alert Emergency Responders and tell them location and nature of hazard.

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.

Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.

- Do NOT cut, drill, grind or weld such containers.
- In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

### RECOMMENDED STORAGE METHODS

- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

| Source                                                 | Material                                                                                     | TWA ppm | TWA mg/m <sup>3</sup> | STEL ppm | STEL mg/m <sup>3</sup> | Peak ppm | Peak mg/m <sup>3</sup> | TWA F/CC | Notes |
|--------------------------------------------------------|----------------------------------------------------------------------------------------------|---------|-----------------------|----------|------------------------|----------|------------------------|----------|-------|
| Canada - British Columbia Occupational Exposure Limits | cholesteryl acetate (Particles Insoluble or Poorly Soluble) Not Otherwise Classified (PNOC)) |         | 10 (N)                |          |                        |          |                        |          |       |
| US - Wyoming Toxic and Hazardous Substances            | cholesteryl acetate (Particulates not otherwise                                              |         | 5                     |          |                        |          |                        |          |       |

|                                                                           |                                                                                           |    |  |                                                                                                                                                                                 |
|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|----|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Table Z1 Limits for Air Contaminants                                      | regulated (PNOR)(f)-Respirable fraction)                                                  |    |  |                                                                                                                                                                                 |
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants | cholesteryl acetate (Particulates not otherwise regulated Respirable fraction)            | 5  |  |                                                                                                                                                                                 |
| US - California Permissible Exposure Limits for Chemical Contaminants     | cholesteryl acetate (Particulates not otherwise regulated Respirable fraction)            | 5  |  | (n)                                                                                                                                                                             |
| US - Oregon Permissible Exposure Limits (Z-1)                             | cholesteryl acetate (Particulates not otherwise regulated (PNOR) (f) Total Dust)          | 10 |  | Bold print identifies substances for which the Oregon Permissible Exposure Limits (PELs) are different than the federal Limits. PNOR means "particles not otherwise regulated." |
| US - Michigan Exposure Limits for Air Contaminants                        | cholesteryl acetate (Particulates not otherwise regulated, Respirable dust)               | 5  |  |                                                                                                                                                                                 |
| Canada - Prince Edward Island Occupational Exposure Limits                | cholesteryl acetate (Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles)   | 10 |  | See Appendix B current TLV/BEI Book                                                                                                                                             |
| US - Oregon Permissible Exposure Limits (Z-1)                             | cholesteryl acetate (Particulates not otherwise regulated (PNOR) (f) Respirable Fraction) | 5  |  | Bold print identifies substances for which the Oregon Permissible Exposure Limits (PELs) are different than the federal Limits. PNOR means "particles not otherwise regulated." |

ENDOELTABLE

## PERSONAL PROTECTION



## RESPIRATOR

Particulate

Consult your EHS staff for recommendations

## EYE

- Safety glasses with side shields.
- Chemical goggles.

## HANDS/FEET

■ Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene
- nitrile rubber
- butyl rubber
- fluorocarbon
- polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

## OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

## ENGINEERING CONTROLS

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### PHYSICAL PROPERTIES

Solid.

Does not mix with water.

|                           |                |                                |                 |
|---------------------------|----------------|--------------------------------|-----------------|
| State                     | Divided solid  | Molecular Weight               | 428.70          |
| Melting Range (°F)        | 233.6- 237.2   | Viscosity                      | Not Applicable  |
| Boiling Range (°F)        | Not available  | Solubility in water (g/L)      | Partly miscible |
| Flash Point (°F)          | Not available  | pH (1% solution)               | Not applicable  |
| Decomposition Temp (°F)   | Not available. | pH (as supplied)               | Not applicable  |
| Autoignition Temp (°F)    | Not available  | Vapour Pressure (mmHG)         | Negligible      |
| Upper Explosive Limit (%) | Not available. | Specific Gravity (water=1)     | Not available   |
| Lower Explosive Limit (%) | Not available  | Relative Vapor Density (air=1) | Not Applicable  |
| Volatile Component (%vol) | Negligible     | Evaporation Rate               | Not applicable  |

### APPEARANCE

White crystalline powder; does not mix well with water. Soluble in chloroform.

## Section 10 - CHEMICAL STABILITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

### STORAGE INCOMPATIBILITY

- Avoid reaction with oxidizing agents.
- Cholesterol may undergo autooxidation and photo-oxidation, both processes give rise to oxysterols of various structures depending on the type of oxidation and the physical state of the substrate.
- The identification of cholesterol oxidation products may be used as a mechanistic proof in various oxidant systems.
- When cholesterol esters are oxidised, the structure and the yield of the formed oxysterols depend on the fatty acid species.

For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

cholesteryl acetate

### TOXICITY AND IRRITATION

#### CHOLESTERYL ACETATE:

- No significant acute toxicological data identified in literature search.

## Section 12 - ECOLOGICAL INFORMATION

No data

### Ecotoxicity

|                     |                         |                  |                 |          |
|---------------------|-------------------------|------------------|-----------------|----------|
| Ingredient          | Persistence: Water/Soil | Persistence: Air | Bioaccumulation | Mobility |
| cholesteryl acetate | HIGH                    |                  | LOW             | LOW      |

## Section 13 - DISPOSAL CONSIDERATIONS

### Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

## Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

## Section 15 - REGULATORY INFORMATION

**cholesteryl acetate (CAS: 604-35-3) is found on the following regulatory lists;**

"Canada Domestic Substances List (DSL)", "US Toxic Substances Control Act (TSCA) - Inventory"

## Section 16 - OTHER INFORMATION

ND

Substance CAS Suggested codes cholesteryl acetate 604- 35- 3 AUTOID~

*Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.*

*For additional technical information please call our toxicology department on +800 CHEMCALL.*

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: Dec-22-2009

Print Date: Feb-23-2011