

1,1,4,7,10,10-Hexamethyltriethylenetetramine

sc-229812



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION


PRODUCT NAME

1,1,4,7,10,10-Hexamethyltriethylenetetramine

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Santa Cruz Biotechnology, Inc.
2145 Delaware Avenue
Santa Cruz, California 95060
800.457.3801 or 831.457.3800

EMERGENCY

ChemWatch

Within the US & Canada: 877-715-9305

Outside the US & Canada: +800 2436 2255

(1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

C12-H30-N4, [-CH2N(CH3CH2CH2N(CH3)2)2], "1, 2-ethanediamine, N, N' -bis[2-diethylamino]ethyl]-N, N' -dimethyl-", "N, N' -bis[2-(diethylamino)ethyl]-N, N' -dimethyl-1, 2-ethanediamine", "triethyltetramine, 1, 1, 4, 7, 10, 10-hexamethyl-", alkylamine

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS

		Min	Max
Flammability:	1		
Toxicity:	2		
Body Contact:	4		
Reactivity:	1		
Chronic:	2		
			Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4



CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Causes severe burns.

Risk of serious damage to eyes.

May cause SENSITISATION by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion.

■ Ingestion of alkaline corrosives may produce burns around the mouth, ulcerations and swellings of the mucous membranes, profuse saliva production, with an inability to speak or swallow.

Both the esophagus and stomach may experience burning pain; vomiting and diarrhea may follow.

■ Accidental ingestion of the material may be damaging to the health of the individual.

■ Ingestion of amine epoxy-curing agents (hardeners) may cause severe abdominal pain, nausea, vomiting or diarrhea.

The vomitus may contain blood and mucous.

EYE

■ If applied to the eyes, this material causes severe eye damage.

■ Direct eye contact with corrosive bases can cause pain and burns.

There may be swelling, epithelium destruction, clouding of the cornea and inflammation of the iris.

■ Vapors of volatile amines irritate the eyes, causing excessive secretion of tears, inflammation of the conjunctiva and slight swelling of the cornea, resulting in "halos" around lights.

This effect is temporary, lasting only for a few hours.

■ The material can produce severe chemical burns to the eye following direct contact.

Vapors or mists may be extremely irritating.

SKIN

■ The material can produce severe chemical burns following direct contact with the skin.

■ Skin contact is not thought to have harmful health effects, however the material may still produce health damage following entry through wounds, lesions or abrasions.

■ Skin contact with alkaline corrosives may produce severe pain and burns; brownish stains may develop.

The corroded area may be soft, gelatinous and necrotic; tissue destruction may be deep.

■ Open cuts, abraded or irritated skin should not be exposed to this material.

■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

■ Amine epoxy-curing agents (hardeners) may produce primary skin irritation and sensitization dermatitis in predisposed individuals.

Cutaneous reactions include erythema, intolerable itching and severe facial swelling.

INHALED

■ The material can cause respiratory irritation in some persons.

The body's response to such irritation can cause further lung damage.

■ Inhaling corrosive bases may irritate the respiratory tract.

Symptoms include cough, choking, pain and damage to the mucous membrane.

■ Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

■ Inhalation hazard is increased at higher temperatures.

CHRONIC HEALTH EFFECTS

■ Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue.

Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Skin contact with the material is more likely to cause a sensitization reaction in some persons compared to the general population.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

There is some evidence that inhaling this product is more likely to cause a sensitization reaction in some persons compared to the general population.

Inhalation of epoxy resin amine hardeners (including polyamines and amine adducts) and may produce bronchospasm and coughing episodes lasting several days after cessation of the exposure. Even faint traces of these vapors may trigger an intense reaction in individuals showing "amine asthma".

Both secondary amines and tertiary amines can be nitrosated by nitrosating agents to yield nitrosamines. In the case of tertiary amines, the mechanism involves intermediate conversion of the tertiary amine to a secondary amine.

Some types of nitrosamines have been shown to be carcinogenic in tests using laboratory animals. In general, all nitrosamines are presumed to be carcinogenic unless they've been tested and shown to be relatively harmless. Nitrosamines are often generated as undesired byproducts in certain foods (especially bacon) and cosmetic and hygiene products (such as shampoo and hair conditioner).

The occurrence of significant levels of nitrosamines in commercial products is normally not accepted. In formulations which contain nitrosating agents, formation of nitrosamines can become a concern where secondary and/or tertiary amines are used as pH control agents.

The most typical nitrosating agents added to formulations are nitrite salts such as sodium or potassium nitrite. Such nitrites are generally added as corrosion inhibitors. Formation of nitrosamine contaminants in such formulations usually results from the reaction of such nitrosating agents with secondary and/or tertiary amines. Nitrosation can occur during product preparation, either during heating or at moderate temperatures. It can also occur while a product sits on a shelf, especially if the product sits for months in a warehouse that becomes warm. Many efforts have been made to eliminate nitrosamines from various substances, or to reduce their concentrations to the lowest practical levels. In various types of food, the use of ascorbic acid (vitamin C) and alpha-tocopherol (vitamin E) and their salts is known to inhibit nitrosamine formation.

In animal experiments the oesophagus is shown to be the most important target organ for nitrosamines, independent of the route of application. The mechanism of this organotrophy cannot be explained sufficiently. The high oesophageal epithelium metabolic activation of nitrosamines, together with a comparatively low DNA repair, probably plays the most important role. In addition chronic stress factors, which lead to high stimulation of epithelial turnover, are a pacemaker for malignant progression. In some countries, the traditional consumption of extremely hot drinks leads to constant burns of the oesophagus, which increases the risk. Mate, a non-alcoholic brew, frequently consumed as tea in Uruguay, appears to be a high risk factor for oesophageal cancer.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
1,1,4,7,10,10-hexamethyltriethylenetetramine	3083-10-1	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

· For advice, contact a Poisons Information Center or a doctor at once. · Urgent hospital treatment is likely to be needed.

EYE

■ If this product comes in contact with the eyes: · Immediately hold eyelids apart and flush the eye continuously with running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

■ If skin or hair contact occurs: · Immediately flush body and clothes with large amounts of water, using safety shower if available. · Quickly remove all contaminated clothing, including footwear.

INHALED

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested. Inhalation of vapors or aerosols (mists, fumes) may cause lung edema. Corrosive substances may cause lung damage (e.g.

NOTES TO PHYSICIAN

■ Treat symptomatically.

For acute or short-term repeated exposures to highly alkaline materials:

· Respiratory stress is uncommon but present occasionally because of soft tissue edema.

· Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Not available
Upper Explosive Limit (%):	Not available
Specific Gravity (water=1):	0.847
Lower Explosive Limit (%):	Not available

EXTINGUISHING MEDIA

· Foam.

· Dry chemical powder.

FIRE FIGHTING

· Alert Emergency Responders and tell them location and nature of hazard.

· Wear full body protective clothing with breathing apparatus.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

· Combustible.

· Slight fire hazard when exposed to heat or flame.

Combustion products include: carbon dioxide (CO₂), nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:

Full face- shield.

Gloves:

Respirator:

Type AB-P Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.
 - Check regularly for spills and leaks.
 - Clean up all spills immediately.
 - Avoid breathing vapors and contact with skin and eyes.
- MAJOR SPILLS**
- Clear area of personnel and move upwind.
 - Alert Emergency Responders and tell them location and nature of hazard.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.

RECOMMENDED STORAGE METHODS

- Lined metal can, Lined metal pail/drum
 - Plastic pail.
- For low viscosity materials
- Drums and jerricans must be of the non-removable head type.
 - Where a can is to be used as an inner package, the can must have a screwed enclosure.

STORAGE REQUIREMENTS

- Store in original containers.
 - Keep containers securely sealed.
- DO NOT store near acids, or oxidizing agents.
- No smoking, naked lights, heat or ignition sources.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- 1,1,4,7,10,10-hexamethyltriethylenetetramine: CAS:3083-10-1

PERSONAL PROTECTION



RESPIRATOR

Type AB-P Filter of sufficient capacity
Consult your EHS staff for recommendations

EYE

- Chemical goggles.
- Full face shield.

HANDS/FEET

- Elbow length PVC gloves.

- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

NOTE: The material may produce skin sensitization in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.

- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- Neoprene gloves.

OTHER

- Overalls.
- PVC Apron.

ENGINEERING CONTROLS

- Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Liquid.
Does not mix with water.
Floats on water.
Corrosive.

State	Liquid	Molecular Weight	230.40
Melting Range (°F)	Not available	Viscosity	Not Available
Boiling Range (°F)	266 (11 mm Hg)	Solubility in water (g/L)	Partly miscible
Flash Point (°F)	215	pH (1% solution)	Not applicable.
Decomposition Temp (°F)	Not available.	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Not available
Upper Explosive Limit (%)	Not available	Specific Gravity (water=1)	0.847
Lower Explosive Limit (%)	Not available	Relative Vapor Density (air=1)	>1
Volatile Component (%vol)	Not available	Evaporation Rate	Not available

APPEARANCE

Colourless liquid; does not mix well with water.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

STORAGE INCOMPATIBILITY

- Avoid strong acids.
 - Avoid contact with copper, aluminium and their alloys.
- Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

1,1,4,7,10,10-hexamethyltriethylenetetramine

TOXICITY AND IRRITATION

1,1,4,7,10,10-HEXAMETHYLTRIETHYLENETETRAMINE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY IRRITATION

Oral (quail) LD50: >316 mg/kg Nil Reported

- Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's edema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

Section 12 - ECOLOGICAL INFORMATION

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.
Refer to special instructions/ safety data sheets.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
1,1,4,7,10,10-hexamethyltriethylenetetramine	HIGH		LOW	MED

Section 13 - DISPOSAL CONSIDERATIONS

US EPA Waste Number & Descriptions

A. General Product Information

Corrosivity characteristic: use EPA hazardous waste number D002 (waste code C)

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols: None Hazard class or Division: 8

Identification Numbers: UN2735 PG: II

Label Codes: 8 Special provisions: B2, IB2,

T11, TP1,

TP27

Packaging: Exceptions: 154 Packaging: Non- bulk: 202

Packaging: Exceptions: 154 Quantity limitations: 1 L

Passenger aircraft/rail:

Quantity Limitations: Cargo 30 L Vessel stowage: Location: A

aircraft only:

Vessel stowage: Other: 52

Hazardous materials descriptions and proper shipping names:

Amines, liquid, corrosive, n.o.s., or Polyamines, liquid, corrosive, n.o.s.

Air Transport IATA:

ICAO/IATA Class: 8 ICAO/IATA Subrisk: None

UN/ID Number: 2735 Packing Group: II

Special provisions: A3

Cargo Only

Packing Instructions: 30 L Maximum Qty/Pack: 1 L

Passenger and Cargo Passenger and Cargo

Packing Instructions: 855 Maximum Qty/Pack: 851

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: 0.5 L Maximum Qty/Pack: Y840

Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. *

(CONTAINS 1,1,4,7,10,10-HEXAMETHYLTRIETHYLENETETRAMINE)

Maritime Transport IMDG:

IMDG Class: 8 IMDG Subrisk: None

UN Number: 2735 Packing Group: II

EMS Number: F-A , S-B Special provisions: 274

Limited Quantities: 1 L Marine Pollutant: Yes
Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. 8
(contains 1,1,4,7,10,10-hexamethyltriethylenetetramine)

Section 15 - REGULATORY INFORMATION

1,1,4,7,10,10-hexamethyltriethylenetetramine (CAS: 3083-10-1) is found on the following regulatory lists;
"Canada Non-Domestic Substances List (NDSL)", "US Toxic Substances Control Act (TSCA) - Inventory"

Section 16 - OTHER INFORMATION

ND

Substance CAS Suggested codes 1, 1, 4, 7, 10, 10- 3083- 10- 1 Xn; R22 R43 Xi; hexamethyltriethylenetetramine R38 R52/53

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Feb-9-2009

Print Date: Mar-10-2011