

2-Acetamidofluorene

sc-253064



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

2-Acetamidofluorene

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Santa Cruz Biotechnology, Inc.
2145 Delaware Avenue
Santa Cruz, California 95060
800.457.3801 or 831.457.3800

EMERGENCY

ChemWatch
Within the US & Canada: 877-715-9305
Outside the US & Canada: +800 2436 2255
(1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

C15-H13-N-O, AAF, 2-AAF, "acetamide, N-9H-fluoren-2-yl-", 2-acetaminofluorene, acetoaminofluorene, N-acetyl-2-aminofluorene, 2-(acetylamino)fluorene, 2-acetylamino fluorene, FAA, 2-FAA, 2-fluorenylacetylamide, N-2-fluorenylacetylamide, N-fluoren-2-ylacetamide, N-9H-fluoren-2-ylacetamide, "RCRA Waste No.: U005"

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS

		Min	Max
Flammability:	1		
Toxicity:	3		
Body Contact:	3		
Reactivity:	1		
Chronic:	3		

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

May cause CANCER.
May cause SENSITISATION by skin contact.
May cause heritable genetic damage.
Possible risk of irreversible effects.
Toxic by inhalation, in contact with skin and if swallowed.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual.
■ The substance and/or its metabolites may bind to hemoglobin inhibiting normal uptake of oxygen. This condition, known as "methemoglobinemia", is a form of oxygen starvation (anoxia).

EYE

■ Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn).
Slight abrasive damage may also result.

SKIN

■ Skin contact with the material may produce toxic effects; systemic effects may result following absorption.
■ The material is not thought to be a skin irritant (as classified using animal models). Abrasive damage however, may result from prolonged exposures.
■ Open cuts, abraded or irritated skin should not be exposed to this material.
■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ Inhalation of dusts, generated by the material, during the course of normal handling, may produce toxic effects.
■ The material is not thought to produce respiratory irritation (as classified using animal models). Nevertheless inhalation of dusts, or fume, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.
■ Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

■ Skin contact with the material is more likely to cause a sensitization reaction in some persons compared to the general population. There is ample evidence that this material can be regarded as being able to cause cancer in humans based on experiments and other information.
Based on experiments and other information, there is ample evidence to presume that exposure to this material can cause genetic defects that can be inherited.
Exposure to the material may result in a possible risk of irreversible effects. The material may produce mutagenic effects in man. This concern is raised, generally, on the basis of appropriate studies using mammalian somatic cells in vivo. Such findings are often supported by positive results from in vitro mutagenicity studies.
Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.
Polycyclic aromatic hydrocarbons are found in a number of materials such as coal tar, tobacco smoke, petroleum and air pollution. Some substituted derivatives have been identified as extremely liable to cause cancer, especially that of the lung and genito-urinary tract.
When incorporated in the diet of rats, 2-acetamidofluorene induced increased incidences of carcinoma of the urinary bladder, subcutaneous carcinoma of the face (possibly originating from the auditory canal), hepatocellular carcinomas, testicular mesotheliomas and Zymbal gland tumours. Mice showed increased incidences of carcinomas in liver and urinary bladder.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
2-acetamidofluorene	53-96-3	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

· Give a slurry of activated charcoal in water to drink. NEVER GIVE AN UNCONSCIOUS PATIENT WATER TO DRINK. · At least 3 tablespoons in a glass of water should be given.

EYE

■ If this product comes in contact with the eyes: · Immediately hold eyelids apart and flush the eye continuously with running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

■ If skin or hair contact occurs: · Quickly but gently, wipe material off skin with a dry, clean cloth. · Immediately remove all contaminated clothing, including footwear.

INHALED

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

NOTES TO PHYSICIAN

■ Treat symptomatically.

The material may induce methemoglobinemia following exposure.

· Initial attention should be directed at oxygen delivery and assisted ventilation if necessary. Hyperbaric oxygen has not demonstrated substantial benefits.

· Hypotension should respond to Trendelenburg's position and intravenous fluids; otherwise dopamine may be needed.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Negligible
Upper Explosive Limit (%):	Not available.
Specific Gravity (water=1):	Not available
Lower Explosive Limit (%):	Not available

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.

FIRE FIGHTING

· Alert Emergency Responders and tell them location and nature of hazard.

· Wear full body protective clothing with breathing apparatus.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

· Combustible solid which burns but propagates flame with difficulty.

· Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

· Clean up waste regularly and abnormal spills immediately.

· Avoid breathing dust and contact with skin and eyes.

· Wear protective clothing, gloves, safety glasses and dust respirator.

· Use dry clean up procedures and avoid generating dust.

· Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).

· Dampen with water to prevent dusting before sweeping.

· Place in suitable containers for disposal.

MAJOR SPILLS

· Clear area of personnel and move upwind.

· Alert Emergency Responders and tell them location and nature of hazard.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
- Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.
- Do NOT cut, drill, grind or weld such containers.
 - In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

RECOMMENDED STORAGE METHODS

- Lined metal can, Lined metal pail/drum
- Plastic pail.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
US - California Permissible Exposure Limits for Chemical Contaminants	2-acetamidofluorene (2-Acetylaminofluorene; N-fluoren-2-yl acetamide; see Section 5209)				12				

ENDOELTABLE

PERSONAL PROTECTION



RESPIRATOR

- particulate.

EYE

- Safety glasses with side shields.
- Chemical goggles.

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.

NOTE: The material may produce skin sensitization in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.

- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.

- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

OTHER

- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area.

- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of

protection may be substituted.

- Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.
- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.
- Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.

ENGINEERING CONTROLS

- Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.
- Work should be undertaken in an isolated system such as a "glove-box" . Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.
- Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.
- Open-vessel systems are prohibited.
- Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.
- Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.
- For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.
- Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).
- Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.
- Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 150 feet/ min. with a minimum of 125 feet/ min. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

State	Divided solid	Molecular Weight	223.28
Melting Range (°F)	378- 385	Viscosity	Not Applicable
Boiling Range (°F)	Not available	Solubility in water (g/L)	Partly miscible
Flash Point (°F)	Not available	pH (1% solution)	Not applicable
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not available.	Specific Gravity (water=1)	Not available
Lower Explosive Limit (%)	Not available	Relative Vapor Density (air=1)	>1
Volatile Component (%vol)	Negligible	Evaporation Rate	Not applicable

APPEARANCE

Light-tan crystalline needles; does not mix well with water. Soluble in alcohols, glycols, ether, acetic acid and fat solvents.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

STORAGE INCOMPATIBILITY

- Avoid oxidizing agents, acids, acid chlorides, acid anhydrides.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

2-acetamidofluorene

TOXICITY AND IRRITATION

2-ACETAMIDOFLUORENE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY	IRRITATION
Oral (mouse) LD50: 810 mg/kg	Nil Reported
Intraperitoneal (mouse) LD50: 470 mg/kg	

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's edema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.

Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen
[National Toxicology Program: U.S. Dep. of Health & Human Services 2002].

Spastic paralysis, altered sleep time, gastrointestinal tumours, fibrous hepatitis, liver tumours, changes in urine composition, bladder tumours, adrenal cortex tumours, paternal effects, effects on fertility, foetotoxicity, specific developmental abnormalities (central nervous system, musculoskeletal system), effects on transplacental tumourigenesis, tumours at site of application recorded.

CARCINOGEN

2-ACETYLAMINOFUORENE	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65
2-ACETYLAMINOFUORENE	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65
VPVB_(VERY~	US - Maine Chemicals of High Concern List	Carcinogen	CA Prop 65; NTP 11th ROC
PBIT_(PERS~	US - Maine Chemicals of High Concern List	Carcinogen	

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
2-acetamidofluorene	HIGH	LOW	LOW	MED

GESAMP/EHS COMPOSITE LIST - GESAMP Hazard Profiles

Name / EHS TRN A1a A1b A1 A2 B1 B2 C1 C2 C3 D1 D2 D3 E1 E2 E3 Cas No / RTECS No _____
_____ Poly(2+)c 224 574 4 4 4 NR (4) NI (1) (1) (2) (1) (1) CM S 3 yclc 6 aromatics / CAS:53- 96- 3 /

Legend: EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships)
NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation, B1=Acuteaquatic toxicity LC/ECIC50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg), C2=Acute mammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion, D2=Eye irritation & corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference with coastal amenities, For column A2: R=Readily biodegradable, NR=Not readily biodegradable. For column D3: C=Carcinogen, M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lunginjury, N=Neurotoxic, I=Immunotoxic. For column E1: NT=Not tainting (tested), T=Tainting test positive. For column E2: Fp=Persistent floater, F=Floater, S=Sinking substances. The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard. (GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships)

Section 13 - DISPOSAL CONSIDERATIONS

US EPA Waste Number & Descriptions

B. Component Waste Numbers

When 2-acetamidofluorene is present as a solid waste as a discarded commercial chemical product, off-specification species, as a container residue, or a spill residue, use EPA waste number U005 (waste code T).

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

‡ Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

· Recycle wherever possible.

· Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - TRANSPORTATION INFORMATION

DOT:

Symbols: None Hazard class or Division: 6.1

Identification Numbers: UN3143 PG: II

Label Codes: 6.1 Special provisions: IB8, IP2,

IP4, T3,

TP33

Packaging: Exceptions: 153 Packaging: Non- bulk: 212

Packaging: Exceptions: 153 Quantity limitations: 25 kg

Passenger aircraft/rail:

Quantity Limitations: Cargo 100 kg Vessel stowage: Location: A

aircraft only:

Vessel stowage: Other: None

Hazardous materials descriptions and proper shipping names:

Dyes, solid, toxic, n.o.s. or Dye intermediates, solid, toxic, n.o.s.

Air Transport IATA:

ICAO/IATA Class: 6.1 ICAO/IATA Subrisk: None

UN/ID Number: 3143 Packing Group: II

Special provisions: A3

Cargo Only

Packing Instructions: 100 kg Maximum Qty/Pack: 676

Passenger and Cargo Passenger and Cargo

Packing Instructions: 25 kg Maximum Qty/Pack: 669

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: 1 kg Maximum Qty/Pack: Y644

Shipping Name: DYE INTERMEDIATE, SOLID, TOXIC, N.O.S. *

†(CONTAINS 2-ACETAMIDOFLUORENE)

Maritime Transport IMDG:

IMDG Class: 6.1 IMDG Subrisk: None

UN Number: 3143 Packing Group: II

EMS Number: F-A , S-A Special provisions: 274

Limited Quantities: 500 g

Shipping Name: DYE, SOLID, TOXIC, N.O.S. or DYE INTERMEDIATE, SOLID, TOXIC, N.O.S.(contains 2-acetamidofluorene)

Section 15 - REGULATORY INFORMATION

2-acetamidofluorene (CAS: 53-96-3) is found on the following regulatory lists;

"Canada - Saskatchewan Industrial Hazardous Substances","Canada Ingredient Disclosure List (SOR/88-64)","Canada Non-Domestic Substances List (NDSL)","Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)","US - Alaska Limits for Air Contaminants","US - California Air Toxics ""Hot Spots"" List (Assembly Bill 2588) Substances for which emissions must be quantified","US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List","US - California Permissible Exposure Limits for Chemical Contaminants","US - California Proposition 65 - Carcinogens","US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens","US - California Toxic Air Contaminant List Category V","US - Connecticut Hazardous Air Pollutants","US - Hawaii Air Contaminant Limits","US - Idaho - Limits for Air Contaminants","US - Maine Chemicals of High Concern List","US - Massachusetts Oil & Hazardous Material List","US - Michigan Exposure Limits for Air Contaminants","US - Minnesota Hazardous Substance List","US - Minnesota Permissible Exposure Limits (PELs)","US - New Jersey Right to Know Hazardous Substances","US - Oregon Permissible Exposure Limits (Z-1)","US - Pennsylvania - Hazardous Substance List","US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants","US - Vermont Hazardous Constituents","US - Vermont Hazardous wastes which are Discarded Commercial Chemical Products or Off-Specification Batches of Commercial Chemical Products or Spill Residues of Either","US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants","US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants","US - Washington Class A toxic air pollutants: Known and Probable Carcinogens","US - Washington Dangerous waste constituents list","US - Washington Discarded Chemical Products List - ""U"" Chemical Products","US - Washington General Occupational Health Standards - List of Carcinogens","US - Washington Permissible exposure limits of air contaminants","US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants","US Clean Air Act - Hazardous Air Pollutants","US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides","US DOE Temporary Emergency Exposure Limits (TEELs)","US EPCRA Section 313 Chemical List","US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act","US National Toxicology Program (NTP) 11th Report Part B. Reasonably Anticipated to be a Human Carcinogen","US NIOSH Recommended Exposure Limits (RELs)","US OSHA Carcinogens Listing","US OSHA Permissible Exposure Levels (PELs) - Table Z1","US RCRA (Resource Conservation & Recovery Act) - Appendix IX to Part 264 Ground-Water Monitoring List 1","US RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261","US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Inorganic and Organic Constituents 1","US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Wastes","US RCRA

Section 16 - OTHER INFORMATION

ND

Substance CAS Suggested codes 2- acetamidofluorene 53- 96- 3 Carc3; R40 Mut3; R68 Xn; R22 R43

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Mar-16-2009

Print Date: May-13-2011