

# 2-(Trifluoroacetoxy)pyridine

sc-254110



The Power to Question

## Material Safety Data Sheet

Hazard Alert Code  
Key:

EXTREME

HIGH

MODERATE

LOW

### Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT NAME

2-(Trifluoroacetoxy)pyridine

#### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

#### NFPA



#### SUPPLIER

Santa Cruz Biotechnology, Inc.  
2145 Delaware Avenue  
Santa Cruz, California 95060  
800.457.3801 or 831.457.3800

#### EMERGENCY

ChemWatch  
Within the US & Canada: 877-715-9305  
Outside the US & Canada: +800 2436 2255  
(1-800-CHEMCALL) or call +613 9573 3112

#### SYNONYMS

C7-H4-F3-N-O2, "2-pyridyl trifluoroacetate"

### Section 2 - HAZARDS IDENTIFICATION

#### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	2	
Toxicity	0	
Body Contact	2	
Reactivity	1	
Chronic	2	

Min/Nil=0  
Low=1  
Moderate=2  
High=3  
Extreme=4



#### CANADIAN WHMIS SYMBOLS



## EMERGENCY OVERVIEW

### RISK

Irritating to eyes, respiratory system and skin.

Flammable.

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion".

This is because of the lack of corroborating animal or human evidence.

##### EYE

■ This material can cause eye irritation and damage in some persons.

■ Pyridine and its derivatives generally produce local irritation on contact with the cornea.

##### SKIN

■ This material can cause inflammation of the skin on contact in some persons.

■ The material may accentuate any pre-existing dermatitis condition.

■ Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

■ Open cuts, abraded or irritated skin should not be exposed to this material.

■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

##### INHALED

■ The material can cause respiratory irritation in some persons.

The body's response to such irritation can cause further lung damage.

■ The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation".

This is because of the lack of corroborating animal or human evidence.

■ Inhalation hazard is increased at higher temperatures.

■ Pyridine and its derivatives generally produce local irritation on contact with the mucous membranes.

Overexposure to pyridine and some of its derivatives may produce headache, nausea, loss of consciousness, nervousness, loss of appetite, sleeplessness and narcosis.

#### CHRONIC HEALTH EFFECTS

■ Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Data from experimental studies indicate that pyridines represent a potential cause of cancer in man. They have also been shown to cross the placental barrier in rats and cause premature delivery, miscarriages and stillbirths. PAs are passed through breast milk. Pyridine has been implicated in the formation of liver cancers.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
2-(trifluoroacetoxy)pyridine	96254-05-6	>98

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

### EYE

If this product comes in contact with the eyes

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

If skin contact occurs

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

### NOTES TO PHYSICIAN

- Treat symptomatically.

## Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG)	Not available
Upper Explosive Limit (%)	Not available
Specific Gravity (water=1)	1.356
Lower Explosive Limit (%)	Not available

### EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

### GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.

Combustion products include carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), hydrogen fluoride, nitrogen oxides (NO<sub>x</sub>), other pyrolysis products typical of burning organic material.

## **FIRE INCOMPATIBILITY**

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

### **MINOR SPILLS**

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.

### **MAJOR SPILLS**

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

## **Section 7 - HANDLING AND STORAGE**

### **PROCEDURE FOR HANDLING**

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT allow clothing wet with material to stay in contact with skin

### **RECOMMENDED STORAGE METHODS**

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) Drums and jerry cans must be of the non-removable head type. (ii) Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)

### **STORAGE REQUIREMENTS**

- Store in original containers in approved flammable liquid storage area.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.

## **Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

### **EXPOSURE CONTROLS**

The following materials had no OELs on our records

- 2-(trifluoroacetoxy)pyridine CAS96254-05-6

### **PERSONAL PROTECTION**



### RESPIRATOR

•Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 1432000 & 1492001, ANSI Z88 or national equivalent)

### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

### HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
  - Wear safety footwear or safety gumboots, eg. Rubber
- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include
- frequency and duration of contact,
  - chemical resistance of glove material,
  - glove thickness and
  - dexterity

### OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

### ENGINEERING CONTROLS

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### PHYSICAL PROPERTIES

Does not mix with water.

Sinks in water.

State	LIQUID	Molecular Weight	191.11
-------	--------	------------------	--------

Melting Range (°F)	Not available	Viscosity	Not Available
Boiling Range (°F)	~140 (0.3 mm Hg)	Solubility in water (g/L)	Partly miscible
Flash Point (°F)	120	pH (1% solution)	Not applicable
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Not available
Upper Explosive Limit (%)	Not available	Specific Gravity (water=1)	1.356
Lower Explosive Limit (%)	Not available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	Not available	Evaporation Rate	Not available

## APPEARANCE

Liquid; does not mix well with water.

## Section 10 - CHEMICAL STABILITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

### STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents

For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

2-(trifluoroacetoxy)pyridine

### TOXICITY AND IRRITATION

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.
- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

No significant acute toxicological data identified in literature search.

## Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

## Section 13 - DISPOSAL CONSIDERATIONS

### US EPA Waste Number & Descriptions

A. General Product Information

Ignitability characteristic: use EPA hazardous waste number D001 (waste code I)

### Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling

- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

### Section 14 - TRANSPORTATION INFORMATION

DOT:

Symbols:	None	Hazard class or Division:	3
Identification Numbers:	UN1993	PG:	III
Label Codes:	3	Special provisions:	B1, B52, IB3, T4, TP1, TP29
Packaging: Exceptions:	150	Packaging: Non-bulk:	203
Packaging: Exceptions:	150	Quantity limitations: Passenger aircraft/rail:	60 L
Quantity Limitations: Cargo aircraft only:	220 L	Vessel stowage: Location:	A
Vessel stowage: Other:	None		

#### COMBUSTIBLE LIQUID

A flammable liquid with a flash point at or above 38 deg.C (100 deg.F) that does not meet the definition of any other hazard class may be reclassified as a combustible liquid. This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable. An elevated temperature material that meets the definition of a Class 3 material because it is intentionally heated and offered for transportation or transported at or above its flash point may not be reclassified as a combustible liquid.

Refer to 49 CFR 173.120(b)(2)

#### Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1993	Packing Group:	III
Special provisions:	A3		
Cargo Only			
Packing Instructions:	366	Maximum Qty/Pack:	220 L
Passenger and Cargo		Passenger and Cargo	
Packing Instructions:	355	Maximum Qty/Pack:	60 L
Passenger and Cargo Limited Quantity		Passenger and Cargo Limited Quantity	

Packing Instructions:	Y344	Maximum Qty/Pack:	10 L
Shipping name:FLAMMABLE LIQUID, N.O.S.(contains 2-(trifluoroacetoxy)pyridine)			
<b>Maritime Transport IMDG:</b>			
IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1993	Packing Group:	III
EMS Number:	F-E,S-E	Special provisions:	223 274 955
Limited Quantities:	5 L		
Shipping name:FLAMMABLE LIQUID, N.O.S.(contains 2-(trifluoroacetoxy)pyridine)			

### Section 15 - REGULATORY INFORMATION

**2-(trifluoroacetoxy)pyridine (CAS: 96254-05-6) is found on the following regulatory lists;**

"US Department of Transportation (DOT), Hazardous Material Table"

### Section 16 - OTHER INFORMATION

#### LIMITED EVIDENCE

- Cumulative effects may result following exposure\*.
- Limited evidence of a carcinogenic effect\*.

\* (limited evidence).

*Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.*

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at: [www.chemwatch.net/references](http://www.chemwatch.net/references).

- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

[www.chemwatch.net](http://www.chemwatch.net)

Issue Date: Nov-27-2009

Print Date:Dec-9-2011