

Indene

sc-255211

Material Safety Data Sheet



The Power to Question

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Indene

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Santa Cruz Biotechnology, Inc.
2145 Delaware Avenue
Santa Cruz, California 95060
800.457.3801 or 831.457.3800

EMERGENCY:

ChemWatch

Within the US & Canada: 877-715-9305

Outside the US & Canada: +800 2436 2255

(1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

C9-H8, indo-naphthene, indonaphthene

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability:	2	
Toxicity:	2	
Body Contact:	2	
Reactivity:	2	
Chronic:	2	

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

HARMFUL - May cause lung damage if swallowed.
Harmful by inhalation and if swallowed.
Irritating to eyes, respiratory system and skin.
Flammable.
Vapours may cause drowsiness and dizziness.
Toxic to aquatic organisms.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
 - Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).
 - High oral doses are fatal in rats producing characteristic changes in the liver, lungs and gastrointestinal tract.
- Aspiration of liquid indene into the lung produces chemical pneumonitis, pulmonary oedema and haemorrhage in animals.
- At sufficiently high doses the material may be nephrotoxic(i).
- e.

EYE

- This material can cause eye irritation and damage in some persons.

SKIN

- This material can cause inflammation of the skin oncontact in some persons.
 - The material may accentuate any pre-existing dermatitis condition.
 - Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.
 - Open cuts, abraded or irritated skin should not be exposed to this material.
 - Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.
- Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- Inhalation of vapors or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
 - The material can cause respiratory irritation in some persons.
- The body's response to such irritation can cause further lung damage.
- Inhalation of vapours may cause drowsiness and dizziness.
- This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.
- Rats exposed to indene at concentrations of 800-900 ppm for six 7-hour periods showed liver damage, and occasional splenic or renal damage.
- Severe haemorrhagic liver necrosis occurred in some rats.
- Inhalation of high concentrations of gas/vapor causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.
 - Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness.
- Serious poisonings may result in respiratory depression and may be fatal.

CHRONIC HEALTH EFFECTS

- Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.
- Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.
- Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
indene	95-13-6	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

· If swallowed do NOT induce vomiting. · If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. · Avoid giving milk or oils. · Avoid giving alcohol. · If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

■ If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

INHALED

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

NOTES TO PHYSICIAN

■ Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

· Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.

· Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Not available
Upper Explosive Limit (%):	Not available
Specific Gravity (water=1):	1.0
Lower Explosive Limit (%):	0.9

EXTINGUISHING MEDIA

· Foam.
· Dry chemical powder.

FIRE FIGHTING

· Alert Emergency Responders and tell them location and nature of hazard.
· May be violently or explosively reactive.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

· Liquid and vapor are flammable.
· Moderate fire hazard when exposed to heat or flame.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides.

FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:
Chemical goggles.
Gloves:
Respirator:
Type A Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

· Remove all ignition sources.
· Clean up all spills immediately.

MAJOR SPILLS

· Clear area of personnel and move upwind.
· Alert Emergency Responders and tell them location and nature of hazard.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec).
- Avoid splash filling.
- Do NOT use compressed air for filling discharging or handling operations.

The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example.

Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised.

- A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are subject to peroxidation. An expiration date should be determined. The chemical should either be treated to remove peroxides or disposed of before this date.
- The person or laboratory receiving the chemical should record a receipt date on the bottle. The individual opening the container should add an opening date.
- Unopened containers received from the supplier should be safe to store for 18 months.
- Opened containers should not be stored for more than 12 months.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.

RECOMMENDED STORAGE METHODS

- Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid.
- For low viscosity materials (i): Drums and jerricans must be of the non-removable head type. (ii): Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C).

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
 - DO NOT store in pits, depressions, basements or areas where vapors may be trapped.
- Air and light sensitive.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
Canada - Alberta Occupational Exposure Limits	indene (Indene)	10	48						
Canada - British Columbia Occupational Exposure Limits	indene (Indene Revised 2008; 2010)	10							
US NIOSH Recommended Exposure Limits (RELs)	indene (Indene)	10	45						
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	indene (Indene)	10	48						
US ACGIH Threshold Limit Values (TLV)	indene (Indene)	5							TLV Basis: Liver damage
US - Vermont Permissible Exposure Limits Table Z-1-A Final	indene (Indene)	10	45						

Rule Limits for Air Contaminants

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	indene (Indene)	10	45		
US - Minnesota Permissible Exposure Limits (PELs)	indene (Indene)	10	45		
US - California Permissible Exposure Limits for Chemical Contaminants	indene (Indene)	10	48		
US - Hawaii Air Contaminant Limits	indene (Indene)	10	45	15	70
US - Alaska Limits for Air Contaminants	indene (Indene)	10	45		
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	indene (Indene)	10		15	
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	indene (Indene)	10	45	15	70
US - Washington Permissible exposure limits of air contaminants	indene (Indene)	10		20	
Canada - Nova Scotia Occupational Exposure Limits	indene (Indene)	5			TLV Basis: Liver damage
Canada - Prince Edward Island Occupational Exposure Limits	indene (Indene)	5			TLV Basis: Liver damage
Canada - Northwest Territories Occupational Exposure Limits (English)	indene (Indene)	10	47	15	71
US - Michigan Exposure Limits for Air Contaminants	indene (Indene)	10	45		
US - Oregon Permissible Exposure Limits (Z-1)	indene (Indene)	10	45		Bold print identifies substances for which the Oregon Permissible Exposure

Limits (PELs)
are different
than the
federal
Limits.

ENDOELTABLE

PERSONAL PROTECTION



RESPIRATOR

- type a filter of sufficient capacity.

EYE

- Safety glasses with side shields.
- Chemical goggles.

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

OTHER

- Overalls.
- PVC Apron.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

ENGINEERING CONTROLS

- For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Does not mix with water.

State	LIQUID	Molecular Weight	116.2
Melting Range (°F)	32.5 - -1.8	Viscosity	Not Available
Boiling Range (°F)	361	Solubility in water (g/L)	Immiscible
Flash Point (°F)	120	pH (1% solution)	Not applicable
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Not available
Upper Explosive Limit (%)	Not available	Specific Gravity (water=1)	1.0
Lower Explosive Limit (%)	0.9	Relative Vapor Density (air=1)	4.01
Volatile Component (%vol)	100	Evaporation Rate	Not available

APPEARANCE

Pale yellow liquid; does not mix with water. Soluble in most organic solvents. Oxidises readily in air. Forms polymers on exposure to air and sunlight.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

indene

TOXICITY AND IRRITATION

INDENE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY	IRRITATION
Inhalation (rat) LC50: 14000 mg/m ³	Nil Reported
Unr (rat) LD50: 2300 mg/kg	
Unr (mouse) LD50: 1800 mg/kg	
Intraperitoneal (mouse) LD50: 7 mg/kg	

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

CARCINOGEN

indene	US - Rhode Island Hazardous Substance List	IARC	
POLYCYCLIC ORGANIC MATTER (POM)	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	EPA-HEN, P65-MC
PBIT_(PERS~	US - Maine Chemicals of High Concern List	Carcinogen	

Section 12 - ECOLOGICAL INFORMATION

Toxic to aquatic organisms.

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
indene	HIGH	No Data Available	LOW	MED

GESAMP/EHS COMPOSITE LIST - GESAMP Hazard Profiles

Name / EHS TRN A1a A1b A1 A2 B1 B2 C1 C2 C3 D1 D2 D3 E1 E2 E3 Cas No / RTECS No _____
Poly(2+)c 224 574 4 4 NR (4) NI (1) (1) (2) (1) (1) CM S 3 yclc 6 aromatics / CAS:95- 13- 6 /

Legend: EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships)
NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation,

B1=Acuteaquatic toxicity LC/ECIC50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg), C2=Acute mammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion, D2=Eye irritation& corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference with coastal amenities, For column A2: R=Readily biodegradable, NR=Not readily biodegradable. For column D3: C=Carcinogen, M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lung injury, N=Neurotoxic, I=Immunotoxic. For column E1: NT=Not tainting (tested), T=Tainting test positive. For column E2: Fp=Persistent floater, F=Floater, S=Sinking substances. The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard. (GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships)

Section 13 - DISPOSAL CONSIDERATIONS

US EPA Waste Number & Descriptions

A. General Product Information

Ignitability characteristic: use EPA hazardous waste number D001 (waste code I)

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - TRANSPORTATION INFORMATION

DOT:

Symbols: None Hazard class or Division: 3

Identification Numbers: UN3295 PG: III

Label Codes: 3 Special provisions: 144, B1,

IB3, T4,

TP1, TP29

Packaging: Exceptions: 150 Packaging: Non- bulk: 203

Packaging: Exceptions: 150 Quantity limitations: 60 L

Passenger aircraft/rail:

Quantity Limitations: Cargo 220 L Vessel stowage: Location: A

aircraft only:

Vessel stowage: Other: None

COMBUSTIBLE LIQUID

A flammable liquid with a flash point at or above 38 deg.C (100 deg.F) that does not meet the definition of any other hazard class may be

reclassified as a combustible liquid. This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable. An elevated temperature material that meets the definition of a Class 3 material because it is intentionally heated and offered for transportation or transported at or above its flash point may not be reclassified as a combustible liquid. Refer to 49 CFR 173.120(b)(2)

Air Transport IATA:

UN/ID Number: 3295 Packing Group: III

Special provisions: A3

Cargo Only

Packing Instructions: 220 L Maximum Qty/Pack: 366

Passenger and Cargo Passenger and Cargo

Packing Instructions: 60 L Maximum Qty/Pack: 355

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: 10 L Maximum Qty/Pack: Y344

Shipping Name: HYDROCARBONS, LIQUID, N.O.S.(CONTAINS INDENE)

Maritime Transport IMDG:

IMDG Class: 3 IMDG Subrisk: None

UN Number: 3295 Packing Group: III
EMS Number: F-E , S-D Special provisions: 223
Limited Quantities: 5 L
Shipping Name: HYDROCARBONS, LIQUID, N.O.S.(contains indene)

Section 15 - REGULATORY INFORMATION

indene (CAS: 95-13-6) is found on the following regulatory lists;

"Canada - Alberta Occupational Exposure Limits","Canada - British Columbia Occupational Exposure Limits","Canada - Northwest Territories Occupational Exposure Limits (English)","Canada - Nova Scotia Occupational Exposure Limits","Canada - Prince Edward Island Occupational Exposure Limits","Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)","Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits","Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances","Canada Ingredient Disclosure List (SOR/88-64)","Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)","International Fragrance Association (IFRA) Survey: Transparency List","OECD Representative List of High Production Volume (HPV) Chemicals","US - Alaska Limits for Air Contaminants","US - California Permissible Exposure Limits for Chemical Contaminants","US - Connecticut Hazardous Air Pollutants","US - Hawaii Air Contaminant Limits","US - Michigan Exposure Limits for Air Contaminants","US - Minnesota Hazardous Substance List","US - Minnesota Permissible Exposure Limits (PELs)","US - New Jersey Right to Know Hazardous Substances","US - Oregon Permissible Exposure Limits (Z-1)","US - Pennsylvania - Hazardous Substance List","US - Rhode Island Hazardous Substance List","US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants","US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants","US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants","US - Washington Permissible exposure limits of air contaminants","US ACGIH Threshold Limit Values (TLV)","US DOE Temporary Emergency Exposure Limits (TEELs)","US EPA Master Testing List - Index I Chemicals Listed","US NIOSH Recommended Exposure Limits (RELs)","US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory","US TSCA Section 4 (e) - ITC Priority Testing List","US TSCA Section 8 (a) - Preliminary Assessment Information Rules (PAIR) - Reporting List","US TSCA Section 8 (d) - Health and Safety Data Reporting"

Section 16 - OTHER INFORMATION

LIMITED EVIDENCE

- Potentially explosive peroxides may form on standing.*.
 - Skin contact may produce health damage*.
 - Cumulative effects may result following exposure*.
 - Repeated exposure potentially causes skin dryness and cracking*.
- *(limited evidence).

Denmark Advisory list for selfclassification of dangerous substances

Substance CAS Suggested codes indene 95- 13- 6 Xn; R22 N; R50

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.
A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: May-8-2009

Print Date:Jun-16-2011