# **Diethyl Ethylphosphonate**

sc-294322

**Material Safety Data Sheet** 



The Power to Oscotion

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

### Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

Diethyl Ethylphosphonate

### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

# NFPA FLAMK BILITY HEALTH AZARD INST BLITY

### **SUPPLIER**

Santa Cruz Biotechnology, Inc. 2145 Delaware Avenue Santa Cruz, California 95060 800.457.3801 or 831.457.3800

### **EMERGENCY**:


ChemWatch Within the US & Canada: 877-715-9305 Outside the US & Canada: +800 2436 2255 (1-800-CHEMCALL) or call +613 9573 3112

### **SYNONYMS**

C6-H15-O3-P, diethylethylphosphonate, "diethoxyethylphosphine oxide", "ethyldiethoxyphosphine oxide", "ethanephosphonic acid diethyl ester", "Amgard V 490", "Antiblaze 75", "Antiblaze V490", "Levagard AC 4048", DEEP, "fire retardant"

### **Section 2 - HAZARDS IDENTIFICATION**

# **CHEMWATCH HAZARD RATINGS**







### **CANADIAN WHMIS SYMBOLS**



### **EMERGENCY OVERVIEW** RISK

Harmful if swallowed.

Danger of cumulative effects.

Risk of serious damage to eyes.

Irritating to respiratory system and skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### **POTENTIAL HEALTH EFFECTS**

### **ACUTE HEALTH EFFECTS**

### **SWALLOWED**

■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

■ If applied to the eyes, this material causes severe eye damage.

- This material can cause inflammation of the skin oncontact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

### **INHALED**

■ The material can cause respiratory irritation in some persons.

The body's response to such irritation can cause further lung damage.

- Inhalation of vapors or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.
- Aliphatic, aromatic and substituted phosphonates exhibit moderate to high toxicity, and toxicity is increased when there are benzene rings and halogen or nitro group substitution.

### **CHRONIC HEALTH EFFECTS**

■ Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS				
NAME	CAS RN	%		
diethyl ethylphosphonate	78-38-6	>98		

### **Section 4 - FIRST AID MEASURES**

### **SWALLOWED**

· IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

■ If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

### SKIN

■ If skin contact occurs: Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

### INHALED

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

### **NOTES TO PHYSICIAN**

■ for poisons (where specific treatment regime is absent):

· Establish a patent airway with suction where necessary.

· Watch for signs of respiratory insufficiency and assist ventilation as necessary.

Section 5 - FIRE FIGHTING MEASURES				
Vapor Pressure (mmHg):	7.501 mbar (20 C)			
Upper Explosive Limit (%):	Not Available			
Specific Gravity (water=1):	1.028			
Lower Explosive Limit (%):	Not Available			

### **EXTINGUISHING MEDIA**

- · Foam.
- · Dry chemical powder.

### **FIRE FIGHTING**

- · Alert Emergency Responders and tell them location and nature of hazard.
- · Wear full body protective clothing with breathing apparatus.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

### GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- · Combustible.
- · Slight fire hazard when exposed to heat or flame.

Combustion products include: carbon dioxide (CO2), phosphorus oxides (POx), other pyrolysis products typical of burning organic material.

Phosphorus-containing flame retardants effectively work in the solid phase of burning materials (as distinct from the burning gas above them). When heated the phosphorus reacts to give a polymeric form of phosphoric acid. This acid causes the material to char, forming a glassy layer, and thus inhibits the "pyrolysis" process (which causes breakdown of the solid to release flammable gases which further fuel the fire).

### FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids,chlorine bleaches, pool chlorine etc. as ignition may result.

### PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Type A Filter of sufficient capacity

### Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- Environmental hazard contain spillage.
- · Clean up all spills immediately.
- · Avoid breathing vapors and contact with skin and eyes.

MAJOR SPILLS

■ Environmental hazard - contain spillage.

Moderate hazard.

- $\cdot$  Clear area of personnel and move upwind.
- · Alert Emergency Responders and tell them location and nature of hazard.

### **Section 7 - HANDLING AND STORAGE**

### PROCEDURE FOR HANDLING

- · DO NOT allow clothing wet with material to stay in contact with skin.
- · Avoid all personal contact, including inhalation.
- · Wear protective clothing when risk of exposure occurs.

### **RECOMMENDED STORAGE METHODS**

- · Metal can or drum
- $\cdot \ \text{Packing as recommended by manufacturer}.$

### STORAGE REQUIREMENTS

- Store in original containers.
- · Keep containers securely sealed.

### Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### **EXPOSURE CONTROLS**

The following materials had no OELs on our records

• diethyl ethylphosphonate: CAS:78-38-6

### PERSONAL PROTECTION









### **RESPIRATOR**

· type a filter of sufficient capacity.

### **EYE**

- · Safety glasses with side shields.
- · Chemical goggles.

### HANDS/FEET

■ Wear chemical protective gloves, eg. PVC.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- · frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- · dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- · Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

### **OTHER**

- · Overalls.
- · P.V.C. apron.
- · Barrier cream.
- · Skin cleansing cream.
- · Eye wash unit.

### **ENGINEERING CONTROLS**

■ Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator.

### **Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

### **PHYSICAL PROPERTIES**

Liquid.

Mixes with water.

State	Liquid	Molecular Weight	166.156
Melting Range (°F)	Not Available	Viscosity	2~ (20 C) cSt@40°C
Boiling Range (°F)	385~; 202	Solubility in water (g/L)	Miscible
Flash Point (°F)	>392	pH (1% solution)	Not Available
Decomposition Temp (°F)	518	pH (as supplied)	Not Applicable
Autoignition Temp (°F)	500	Vapor Pressure (mmHg)	7.501 mbar (20 C)
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.028
Lower Explosive Limit (%)	Not Available	Relative Vapor Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

### **APPEARANCE**

Clear liquid with characteristic odour; mixes with water.

### **Section 10 - CHEMICAL STABILITY**

### CONDITIONS CONTRIBUTING TO INSTABILITY

- · Presence of incompatible materials.
- · Product is considered stable.

### STORAGE INCOMPATIBILITY

■ Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

### **Section 11 - TOXICOLOGICAL INFORMATION**

diethyl ethylphosphonate

### **TOXICITY AND IRRITATION**

DIETHYL ETHYLPHOSPHONATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY IRRITATION

Oral (Rat) LD50: 2330 mg/kg Eyes (rabbit): SEVERE \*\*

Oral (Mouse) LD50: 2500 mg/kg Skin (rabbit): slight (4 h) \*\*

Oral (Rat) LD50: 785 mg/kg mg/kg \*
Dermal (Rat) LD50: >2000 mg/kg \*

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

No indication of mutagenic effect \*\*

### **Section 12 - ECOLOGICAL INFORMATION**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

Refer to special instructions/ safety data sheets.

### **Ecotoxicity**

Persistence: Air Bioaccumulation Mobility

Water/Soil

diethyl ethylphosphonate HIGH

No Data
Available

LOW
HIGH

### **Section 13 - DISPOSAL CONSIDERATIONS**

### **Disposal Instructions**

All waste must be handled in accordance with local, state and federal regulations.

| Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

<sup>\*</sup> Sigma Aldrich SDS

<sup>\*\*</sup> Bayer SDS

A Hierarchy of Controls seems to be common - the user should investigate:

- · Reduction
- · Reuse
- · Recycling
- · Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- · Recycle wherever possible or consult manufacturer for recycling options.
- · Consult Waste Management Authority for disposal.

### Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols: G Hazard class or Division: 9 Identification Numbers: UN3082 PG: III Label Codes: 9 Special provisions: 8, 146,

335, IB3, T4, TP1, TP29

Packaging: Exceptions: 155 Packaging: Non- bulk: 203 Packaging: Exceptions: 155 Quantity limitations: No limit

Passenger aircraft/rail:

Quantity Limitations: Cargo No limit Vessel stowage: Location: A

aircraft only:

Vessel stowage: Other: None

Hazardous materials descriptions and proper shipping names:

Environmentally hazardous substance, liquid, n.o.s

Air Transport IATA:

ICAO/IATA Class: 9 ICAO/IATA Subrisk: None UN/ID Number: 3082 Packing Group: III

Special provisions: A97

Cargo Only

Packing Instructions: 450 L Maximum Qty/Pack: 964 Passenger and Cargo Passenger and Cargo Packing Instructions: 450 L Maximum Qty/Pack: 964

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: 30 kg G Maximum Qty/Pack: Y964

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. \*(CONTAINS DIETHYL ETHYLPHOSPHONATE)

# Maritime Transport IMDG:

IMDG Class: 9 IMDG Subrisk: None UN Number: 3082 Packing Group: III

EMS Number: F-A, S-F Special provisions: 179 274 335 909

Limited Quantities: 5 L Marine Pollutant: Yes

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(contains diethyl ethylphosphonate)

## **Section 15 - REGULATORY INFORMATION**

### diethyl ethylphosphonate (CAS: 78-38-6) is found on the following regulatory lists;

"Canada Non-Domestic Substances List (NDSL)", "The Australia Group Export Control List: Chemical Weapons Precursors", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US Toxic Substances Control Act (TSCA) - Inventory"

### **Section 16 - OTHER INFORMATION**

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

  A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references.
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Oct-18-2010 Print Date:May-27-2011